

STRATEGIC DESIGN CODE

Epping Forest District Council

LATTON PRIORY

JULY 2024





Design Code lead authors

Epping Forest District Council, Planning Service



Transport Consultant

Phil Jones Associates (PJA)



Rev	Date	Notes:
VI	02.02.2023	Draft
V2	31.05.2023	Draft
V2	19.07.2023	Draft for APG
V3	10.08.2023	lst edit of draft
V4	06.09.2023	Draft for EFDC Cabinet
V5	24.10.2023	Draft for Consultation
V6	06.01.2024	Draft for Endorsement
V7	01.05.2024	Draft for Publishing
V8	24.07.2024	Final Version
	1	•

Copyright in this document and all contents belongs to Epping Forest District Council except where noted.

This document has been endorsed and holds material planning weight in the consideration of planning decisions for the Latton Priory masterplan area.

Contents

Introduction and background information
Introduction
How to use the design code
Planning context
Site context
Design ambitions
Strategic design code
01/ Strategic design code framework
Framework masterplan
Stewardship framework
02/ Nature
Green infrastructure framework
Water management
03/ Movement
Site-wide sustainable movement
Site-wide vehicular movement
Site-wide street network
Site-wide car parking
Parking design

04/ Public space	42
Public space strategy	42
Street design	44
Junction design	56
Public open space design	60
Play and recreation	62
05/ Built form	64
Block structure and density	64
Building frontages	66
Building heights	70
06/ Identity	72
Wayfinding and sense of place	72
Local character	74
07/ Resources	76
Energy use	76
Adaptability and futureproofing	77
Appendices	
Appendix A: SMF Mandatory Spatial Principles	80
Appendix B: Glossary of terms	90
Appendix C: Image References	94

Executive Summary

This strategic design code has been prepared by the planning team at Epping Forest District Council to guide future development for the Latton Priory Strategic masterplan area. It is based on a vision for a new neighbourhood at Latton Priory that captures key aims of the district and the Harlow and Gilston Garden Town as well as local aspirations.

The code envisages a positive and lasting legacy for new and existing communities. It seeks to ensure that the new development is high-quality, coordinated and integrated into its context. It draws on the Strategic Masterplan Framework and identifies the opportunities of the site and best practice design principles for promoting health, community and social vibrancy and addressing the climate emergency.

With a focus on creating a public realm that serves the current and future needs of people, communities and nature, this code addresses the themes of the National Model Design Code that will have the most bearing on those aspects of placemaking. These include the network of green infrastructure, key streets, open spaces and building frontages.

This code provides site-wide strategies and design requirements for key components of the public realm, set out using principles and rules, illustrated with diagrams and precedent images. This ensures that the vision is translated into practical strategies and design measures that are implemented in future proposals and readily assessed.

By focussing on the strategic elements of the development, and prescribing only their key aspects, the code leaves scope for innovation, creativity and variety in future proposals while embedding the foundations of a place where people and nature can thrive.





INTRODUCTION AND BACKGROUND INFORMATION







Purpose of this document

This endorsed Latton Priory strategic design code forms part of the planning framework for the Latton Priory Strategic Masterplan Area. It is intended for use by residents and stakeholders, those involved in developing planning proposals for the site and those evaluating and monitoring future applications and delivery.

The <u>National Planning Policy Framework (NPPF)</u> <u>2023</u> requires that all local planning authorities produce design guides or codes consistent with the principles set out in the National Design Guide and National Model Design Code, and which reflect local character and design preferences.

The Epping Forest District Local Plan requires design codes to be produced informing detailed proposals for individual sites. As an endorsed document with material planning weight, this design code will inform future proposals for the Latton Priory Masterplan Area in line with national and local policy and guidance.

This design code complements other EFDC policy and guidance and does not take its place. This document should be read in conjunction with the other development framework documents.

Preparation of this document

The Latton Priory Strategic Design Code has been prepared by Epping Forest District Council (EFDC) Planning Service through ongoing collaboration with key planning and delivery authorities including other EFDC teams, Harlow Council, Essex County Council and Harlow and Gilston Garden Town (HGGT).

The local community, including young people from local schools, has also been engaged to help understand the context, identity and their ambitions for the future of the area.

Specialist expertise has been provided by Phil Jones Associates Ltd (PJA) transport consultants and support and input has been provided by the Department for Levelling Up Homes and Communities (DLUHC) and the Design Council.

All delivery documents are required to be reviewed by the Harlow and Gilston Garden Town Quality Review Panel (QRP) from the early stages and throughout the design development. This design code was reviewed by the HGGT QRP in July 2022 and May 2023. Further input was provided by the panel members at a code testing workshop in December 2023.

Community and stakeholder engagement

Stage I: Baseline Analysis and Vision

Review and analysis of previous community engagement under taken for the Strategic Masterplan Framework, to avoid duplication. Supplemented by workshops with officers from EFDC and HGGT partner authorities.

Stage 2: Design Code Production

Workshops focused on public realm design with under-represented age groups including children at local primary and secondary schools, Harlow Youth Council and older people through Voluntary Action Epping Forest.

Stage 3: Draft Design Code Review

The local community and stakeholders were invited to give their feedback on the draft code over a 6-week period from Oct - Dec 2023. This included a project website and digital survey, inperson workshops, exhibitions and forums and a HGGT developer forum. The document was then updated to reflect feedback. Details of the events and feedback received are described in the 'Latton priory Draft Strategic Design Code Community Engagement Report', Dec 2023.

Structure of the code

This design code content reflects relevant policy, guidance, community views and site analysis and is presented in themes that address the design ambitions for the site and the following characteristics identified in the National Model Design Code (NMDC):

Framework masterplan / Land use

Site-specific considerations, land use and stewardship building on the Latton Priory Strategic Masterplan Framework endorsed by EFDC Cabinet on 10 July 2023. The framework masterplan is diagrammatic and illustrates the sitewide strategies and principles of the design code. It illustrates how the design code requirements can be delivered whilst allowing flexibility in detailed design proposals

Nature

Green and blue infrastructure, biodiversity and trees.

Movement

Movement frameworks, street hierarchy, parking design and servicing.

Public Space

Hierarchy of public spaces, key open space design, multi-functional street design and junctions and play and recreation strategy.

Built Form

Block structure, density, typologies, height, building line and roof forms to support high-quality public realm and street and open space hierarchy.

Identity

Key frontages and building groupings to aid wayfinding, hierarchy and locally distinctive identity.

Resources

Designing for flexibility, futureproofing and to withstand climate change and to minimise environmental impact.

How the code is used will depend on who is using it and for what purpose. This flow chart shows the process that might be followed by a designer developing proposals for the site:

Understand the context

Read 'Introduction and background information' as well as other policy and guidance documents referenced there, including the Strategic Masterplan Framework (SMF), 2023.

Understand the spatial approach

2.

3.

4.

5.

6.

Read 'Strategic design code framework' section as well as the mandatory spatial principles in the SMF.

Develop key principles

Review the site-wide strategies and framework section of each theme to develop design principles for the development area.

Develop and refine the proposals

Read other strategic code requirements plus any further detailed design code requirements, including character areas. Requires appropriate multi-disciplinary expertise and creativity.

Check compliance against code requirements.

Ensure no deviation from 'musts'. Where there are deviations from 'shoulds', provide evidence of how an alternative approach more successfully achieves the design ambitions of the code.

Review of design proposals

This will include Quality Review Panel (QRP) review. Any deviations from 'should' requirements to be justified. Community and stakeholder engagement to be undertaken in line with policy.



Example of a typical design code layout



Epping Forest District Local Plan

out strategic policies relating to the Latton Priory Masterplan Area. These are:

Local Plan Policy SP2: Place Shaping

Describes place shaping principles for all Strategic Masterplans and development proposals, including long-term stewardship, promoting healthy and active lifestyles and vibrant communities and integrating and connecting with adjacent communities.

Local Plan Policy SP3: Development and **Delivery of Garden Communities**

Sets out the overarching requirements for HGGT communities, including promotion and execution of the highest quality of planning, design and management of the built and public realm, and producing a step change in modal shift to more sustainable travel patterns.

Local Plan Policy SP4: Garden Communities

Sets out the requirements for the new Garden Town Communities. For Latton Priory this includes:

- A minimum of 1,050 homes up to 2033
- Up to one ha of employment land
- Five traveller pitches
- Strategic natural greenspace
- Public open space to the South of the 'build-to' line within the Masterplan Area
- A local centre
- A new primary school with early years and childcare provision.
- At least 10 ha of land to accommodate a secondary school
- Appropriate community and health facilities
- · Highway and transport improvements including a North-South Sustainable Transport Corridor
- · Bus services and direct pedestrian and cycle links between homes, the facilities that serve them and other key destinations.

The Epping Forest District Local Plan 2011-2033 sets The Local Plan also includes detailed policies on Housing, Economy, Transport and Development Management.

> The Local Plan is supported by endorsed guidance documents that hold material weight as planning considerations. Two key documents are:

EFDC Sustainability Guidance

In 2019, the Council declared a climate emergency and made a commitment to do everything within its power to become a carbon neutral District by 2030. In support of this the Council adopted the EFDC Sustainability Guidance and Checklist, which is applicable to all new development in the District. See also HGGT Sustainability Guidance.

EFDC Green Infrastructure Strategy

The Green Infrastructure (GI) Strategy was adopted in 2020 and provides a framework for the provision of high-quality GI provision across the district, including strategies to mitigate impacts on the Epping Forest Special Area of Conservation

Harlow and Gilston Garden Town

The Local Plan identifies Latton Priory as one of three Garden Town Communities forming part of the Harlow and Gilston Garden Town (HGGT). The other two being Water Lane to the west of Harlow and East Harlow. Full details can be found on the HGGT website.

HGGT principles are aligned with EFDC Policy The following draft documents support the Vision and TCPA Garden City principles and the 'key and are available upon request: principles for healthy growth' are set out in the • HGGT Measures to achieve mode share HGGT Vision document as shown in the diagram below. These principles are supported by objectives HGGT STC Placeshaping principles and strategies in the following core documents: • HGGT Healthy Garden Town Framework



'Key Principles for Healthy Growth' diagram, HGGT Vision (2018)

• HGGT Design Guide

• HGGT Transport Strategy

• HGGT Sustainability Guidance

HGGT Green Infrastructure Framework

• HGGT Latton Priory Access Study

HGGT draft Stewardship Charter

Anticipated planning process

The EFDC Local Plan requires that design codes This flow chart shows how the planning process for are produced for Strategic masterplan areas 'to inform detailed proposals for individual sites'.

This strategic code establishes strategies that apply across the site. It focuses mainly on the public realm i.e. types of streets and open spaces and detailed requirements where these apply across the site regardless of character areas.

It is expected that future reserved matters, detailed or hybrid planning applications will be accompanied or preceded by detailed design codes, which look at character areas within the site and how design responds to these different places within the masterplan. The code will ensure that each character area is distinctive whilst maintaining appropriate consistency and quality across the site and at key nodes and interfaces. As a minimum it will cover:

Landscape design

Key nodes and landscape interfaces Tree and planting palette Material selection

Public Realm

Art Strategy Street Furniture Lighting Design Play and Recreation

Built Form

Specific typologies inc approach to bins, bikes and cars Building lines and thresholds Heights

Identity

Architectural treatment Building relationships at key nodes Landmarks and key frontages

Refer to the National Model Design Code for further design code content and process guidance. development at Latton Priory could come forward. Note that only planning applications give permission to build. All other documents are intended to hold weight in the decision making process for those applications.

Stakeholder Engagement

Community and

and

Panel

Quality Review



Site Context

Site Location

The Latton priory masterplan area is located just south of Harlow, on a ridge overlooking the town. It is 1.7 miles for the civic centre (10 minute cycle) and approximately 3.5 miles (20 mins cycle) from Epping town centre.

As former undeveloped green belt land and an HGGT Community, the site requires wider infrastructure to support sustainable travel from and to key destinations in the wider area. It will be connected to Harlow and the other proposed Garden Town sites through a Sustainable Transport Corridor network as shown below:



Site location plan key

EFDC District boundary
Existing development
Allocated sites / strategic masterplan areas
Existing open space
Proposed site area
Proposed local centre inc schools
Proposed new green space
Sustainable transport corridor (STC) connection^{*}
Harlow LCWIP cycle corridor

- ---- Harlow cycle network (mainly off-road)
- ---- Potential cycle connections on shared roads
- New/ improved infrastructure for enhanced cycling

 \ast Indicative routes shown. Final routes subject to further technical work.

- Railway/ underground station
- Colleges
- Hospitals and health centres
- Town hall/ community
- Shopping centres/ local centres
- Headquarters/ emploment areas
- O District parks/ nature reserves
- Cultural and leisure
- Large sports grounds/ leisure centres



Opportunities and Constraints

The steep topography and views from and to the new development and the surrounding areas will be key considerations in the following ways:

- A build-to-line has been established at the ridgeline and no development shall be located south of this.
- Scale, massing and orientation will need to be sensitively designed to consider topography and the ridgeline.
- Site layout will need to be planned to minimise cut-and-fill and work with existing topography whilst ensuring walking and cycling is accessible and attractive throughout the scheme.
- Topography should be integrated into green and blue infrastructure, using it to positively drive the character of the scheme.
- Expansive views of Harlow to the north and countryside to the south should be capitalised through the site layout and positioning of key open spaces and vistas.

Opportunities and constraints plan key



Existing green space/ recreation

Existing woods and tree planting

//////Existing tree belt/ hedgerow/ field boundary

- Existing play space
 - Distinctive local assets/ features
- Strategic HGGT views (HGGT Design Guide)
- Additional key view opportunities
- - > Existing Road
- Existing PROW/ footbath/ bridleway
 - Existing contour line
- Ridge line/ build-to line
 - Key walking and cycling connection
- 🔶 🔶 Sun path
- —Strategic masterplan boundary*

* Reflects boundary of masterplan area allocation in ado This does not preclude improvements outside of the bou



Strategic Design Code / Latton Priory / JULY 2024

Landscape Character

As a landscape-led development surrounded by countryside, including green-belt land on three sides, proposals must respond positively and make the most of the existing green infrastructure.

Currently, the landscape is predominantly arable fields with woodland bands, small clusters of trees and hedgerow field boundaries. The land slopes from the plateau at the south towards the bowl in which Harlow town centre sits. Gradients are more severe on the northern side of the site.

Ancient woodlands define the eastern edge of the site area and blocks of woodland run northsouth on the site. Significant trees also include a row of Poplar trees on the Dorrington Farm site, close to the ridgeline, and rows of mature trees and hedgerow along the northern boundary. A green wedge from Harlow meets the centre of the northern site boundary. This will be extended and enhanced as part of the development.

Key heritage features include the Rye Hill water tower to the west of the site, an ancient moat site along the southern boundary and the Augustinian Latton Priory building itself.

As well as enhancing existing landscape character and connecting up habitats with ecological corridors, the development must be integrated with the existing and proposed green infrastructure. This should inform the identity of the place and form part of the social structure of the new neighbourhood in line with Frederick Gibberd's original vision for Harlow New Town.

See also:
Nature
Public Spaces
EFDC Local Plan Policy SP2, SP3 and SP4
HGGT Design Guide
EFDC Green Infrastructure Guidance



A.View towards water tower and Dorrington Farm



B.View of Latton Priory farm



C.View of row of Poplar trees at Dorrington farm



Aerial view of Latton Priory strategic masterplan area



D. Expansive view towards Harlow town centre and beyond

Built Character

The built form of the new development must relate positively to the best of Epping and Harlow to form a unique, distinctive identity for the new place. Distinctive buildings should be referenced both for appearance and how they shape the public realm. Contextual precedents should not be copied but referenced and interpreted in an innovative and contemporary way.

Epping

As a historic market town, Epping has some varied and characterful historic built form, particularly along the high street and the surrounding areas. Features include distinctive roof forms and proportions, as well as articulation around doors and windows. There is an opportunity to reference the agrarian setting of the site and the agricultural buildings with distinctive geometric forms, striking materials and relationships between buildings.

Harlow

Harlow has characterful built form in the Old Town and rural lanes as well as in the New Town. The modernist buildings feature simple detailing and a restrained material palette with bold compositions that relate well to the spaces they front. Harlow has a strong culture of progressive contemporary architecture with examples of architecture that creates a strong sense of place whilst avoiding pastiche





Characterful cottage on Buttercross Lane, Epping



Articulation around windows on Epping high street.



Articulated windows on Oddfellows Terrace, Old Harlow.



Strong composition and terraced rhythm at Morley Grove, Little Parndon, Harlow by Gibberd and partners.



Progressive and distinctive interpretation of built form context at Abode, Newhall, Harlow by Procter and Matthews.



Latton Priory and surrounding farmstead buildings.

The ambitions, objectives and requirements reflect key aspects of policy, guidance, site opportunities and constraints and feedback received from community engagement.

This design code focusses on the structural elements of the masterplan layout due to the impact this will have on the new community. However it is expected that these design ambitions will also be considered at the detailed design stage.

The design code for Latton priory will help to deliver a healthy, vibrant place where:

A lively core of schools, amenities and shops supports a thriving and resilient community

An integral network of green routes and spaces connects surrounding landscape and enhances the Green Wedge into Harlow

A variety of uplifting and safe streets and spaces encourage year-round active and healthy lifestyles for all ages

Active and sustainable travel is the most appealing way to get around, including travelling to Harlow and Epping



A lively local centre and network of neighbourhood nodes



A multi-functional, integrated green grid



A high-quality active travel network with a choice of safe and accessible routes

Compact, human-scale built form nestles comfortably into the hillside overlooking Harlow

The art and innovation of Harlow, the market town and pastoral character of Epping inform a **distinctive identity**

The climate emergency is addressed with buildings and spaces that can withstand the changing climate and minimise impact on the environment

There is **flexibility to adapt** to future needs, anticipating changes in travel, work and lifestyles



Spaces that can with stand the changing climate and minimise impact on the environment



Human-scale streets and spaces that are vibrant and encourage active lifestyles



STRATEGIC DESIGN CODE



Key strategies for a thriving and resilient community

- Ensure Latton Priory is a vibrant and walkable neighbourhood with a variety of retail and community facilities, social spaces and employment opportunities.
- Provide high-quality homes, offices, studios and spaces that encourage a range of activity through different times of the day, week and year at the heart of Latton Priory.
- Facilitate interaction between different groups of people to help everyone feel connected to the community and to encourage social cohesion and wellbeing.
- Plan the local centre through community and stakeholder engagement to promote pride, inclusiveness, sharing of resources, use and long-term stewardship.

Design code framework masterplan

The design code framework masterplan illustrates the site-wide strategies and principles of the design code. It incorporates the mandatory spatial principles of the Strategic Masterplan Framework (see Appendix A) and site allocation.

While this design code framework masterplan should be a consideration for future proposals, there is flexibility for detailed proposals to respond to technical analysis and employ innovative design to meet or exceed the design ambitions and other policy requirements.

Key features:

- With a policy requirement of a minimum of 1,050 dwellings across the site, additional density could help to support the viability of services including sustainable transport services, subject to review of environmental and transport impact.
- Strategic green infrastructure required by the Strategic Masterplan Framework includes a Suitable Alternative Natural Green Space (SANG), a new park, community pitches, allotments and a network of green fingers.
- The local centre will include mixed-use employment and community facilities, specialist housing, retail, a new primary and secondary school or an all-through school. The

Local Plan allocation requires the provision of appropriate community and health facilities at Latton Priory. Engagement is ongoing with the Hertfordshire and West Essex Integrated Care Board (ICB), the body responsible for planning for healthcare, who are reviewing options such as new facilities, expansion, reconfiguration or relocation of nearby facilities.

- Neighbourhood nodes and a network of carfree play streets will play a role in providing doorstep play and interaction, safe and attractive choices for active travel between homes and key destinations and variety in street character with a network of human-scale streets.
- A sustainable transport corridor will provide active travel and Bus Rapid Transit connections to key destinations in Harlow and a new connector road will be provided for vehicular and cycle connection to Epping and the MII via the BI393 London Road.

See also:
Nature
Public Spaces
Movement
EFDC Local Plan Policy SP2, SP3 and SP4
HGGT Vision and Design Guide
Latton Priory Strategic Masterplan Framework

Framework masterplan requirements

- I.I Development proposals must include the components shown on the diagram and key opposite. The precise quantity, geometry and alignments of components can be modified to suit technical requirements or best-practice to achieve the Vision and ambitions of the Garden Town community.
- 1.2 Sustainable and active travel routes to and from new and existing key destinations must be shown alongside strategies for delivery where these are outside of the site boundary.
- 1.3 Density must be optimised to support the viability of services, retail and sustainable transport and to make efficient use of land subject to wider environmental and transport impact.
- 1.4 The proposals **must** be shown to respond to all the opportunities and constraints of the site, in particular the gradients and existing topography and sightlines into and out of the development.
- 1.5 'Designing out Crime' principles must be embedded into the layout to promote community cohesion, without reducing vibrancy and permeability.

Illustrative framework masterplan layout showing key spatial components



K	ey strategies for a thriving and resilient community	Ste
•	Encourage social interaction and wellbeing, helping to ensure that everyone feels connected and part of the wider community.	l.6 i
•	Promote pride, inclusiveness, sharing of resources, vibrancy and long-term stewardship through community and stakeholder engagement.	1
•	Ensure the public realm can be easily maintained and adapted over the long term, while demonstrating social, economical and ecological consideration and current best practice.	I.7 . I
an de ^r int	e endorsed HGGT Stewardship Charter provides overview of six key stewardship principles that velopers should follow to integrate stewardship o the process of planning, design, delivery, vernance, quality assurance and care of the new	۵ ۲ ۲ ۲
	ghbourhood. The requirements identified here mplement these principles.	I.8 t

See also:	
Nature	
Public Spaces	
Movement - Street design	
Resources	
EFDC Local Plan Policy SP2 and SP3	
EFDC Statement of Community Involvement	
HGGT Quality Monitoring Framework	
HGGT Stewardship Charter	
HGGT Comms and Engagement Strategy	
Make Space for Girls	
Active Design Guidance, Sport England	



Participatory design with local school children

wardship framework requirements

- Community assets must be clearly identified in applications, including those that will benefit the wider community, along with potential safe and accessible active travel routes there. This should include components identified opposite.
- At each phase, community assets must be planned and designed with appropriate expertise and through inclusive engagement with neighbouring residents and intended user groups; this **must** include under-represented and harder-to-reach groups, particularly young people, older people, women and those with reduced mobility.
- Phasing of community assets must be planned to be in place in time for its users to benefit from it or each tranche of new residents will benefit from assets that can facilitate a community and integration with neighbours from the outset. This could include a meanwhile strategy.
- 1.9 Asset management plans must be provided for all public realm and community assets. These must include plans showing each element, the ownership, their use (i.e. social, ecological or economic value), maintenance status and detail on endowments, Section 106 and income generation streams that will allow for on-going maintenance of those assets.
- 1.10 Design of public realm must include information on all key materials and how maintenance, futureproofing and sustainability has been considered in the specification e.g. avoiding power tools, fertilisers and irrigation.
- I.II The extent of public realm that needs to be managed by private householders must be minimised.
- 1.12 Public realm must be designed to ensure maintenance boundaries are clear, but without unnecessary restrictions to access, movement or visual connectivity.

Illustrative framework masterplan layout showing key community assets



Community Assets

 \bigcirc

Green infrastructure assets

Wetland park edge

Community plaza

social spaces

← Car-free play street

Built community assets

Mobility hubs

Car barns Park pavilion

Community buildings

O Play spaces

Gateway spaces

Greenway

Green edges Street and open space assets

Key strategies for an integral network of green routes and spaces

- Use the sloping topography and natural assets of the existing site to create a rich and attractive network of open spaces that people can enjoy and where wildlife can thrive.
- Create a variety of green and open spaces (in type and function) that are accessible to everyone. Allow these to drive the form and character of the new neighbourhood, including its relationship with nearby communities.

Generous, high-quality green and blue infrastructure A connected network of multifunctional blue and will significantly contribute to air quality, net-zero green infrastructure embedded in development and nature recovery as well as the social fabric of areas will: the new community. This will mark Latton Priory out as a Garden Town that celebrates its setting between town and countryside.

- maximise green outlook for homes
- provide ecological and SuDS corridors
- make nature part of every day life
- provide healthy, attractive active travel routes
- encourage vibrancy and outdoor activity
- aid placemaking and wayfinding
- reduce the urban heat island effect

See also: Public Spaces – Multi-functional streets, Play Movement – Street design Resources – Adaptability and futureproofing EFDC Local Plan Policy SP6, DMI-DM3, DM5, DM6 EFDC Green Infrastructure Strategy, Parts 2 and 3 EFDC/ HGGT Sustainability Guidance HGGT Green Infrastructure Framework HGGT Vision and Design Guide Essex Green Infrastructure Standards Essex SuDS Design Guide Green Infrastructure Design Guide, Natural England Trees in Hard Landscapes: a guide for delivery, TDAG

Harlow concept plan showing integrated nature by Sir Frederick Gibberd

Site-wide green infrastructure requirements

- 2.1 Detailed design codes for site-wide coordinated green infrastructure and public realm **must** be provided and endorsed for the whole masterplan area in advance of, or at the same time as any full planning or Reserved Matters Application.
- 2.2 Green infrastructure proposals must be developed collaboratively by qualified landscape architects, ecologists, SuDS engineers, architects and other expertise that may be required. Proposals **must** be developed with the Council and other stakeholders. Engagement with the Council's quality review panel (QRP) must be sought at key stages.
- 2.3 Proposals must demonstrate how neighbouring communities and wildlife will be included and connected with. This must include details of enhancements outside the site boundary as well as mapping of the ecological network.
- 2.4 Urban Greening Factor (UGF) in development areas must be maximised and proposals must achieve a minimum UGF score of 0.5.
- 2.5 Green infrastructure should comprise the components and general alignments shown on the diagram opposite.

02/ Nature Green infrastructure framework

Illustrative green infrastructure framework plan showing key components, routes and character areas

Key green infrastructure routes

- Greenway
- Greenway through local centre
- Latton Avenue alongside green finger
- North-south green finger/ green wedge
- $\bullet \bullet \bullet \bullet$ Street greenery inc biodiversity planting and street trees*
 - Feature trees or tree clusters at key nodes and vistas (shown indicatively)
- Key green infrastructure interfaces
 - Wetland park edge
 - Woodland edge
 - Ridgline edge
 - Rye Hill road edge
 - Key edges
 - Existing woods

///////Tree belt/ hedgerow/ field boundary

– – Ridge line/ build-to line

Main landscape character areas

- Southern plateau
- Eastern woodlands
- Central green wedge and green ways
- **Wetlands**

*Street trees on neighbourhood/ local streets not shown here.

N.B Contours depict existing topography and should be updated following earthworks analysis



New park requirements

The new park will extend the green wedge and will attract visitors and provide social infrastructure that benefits new and existing communities. It will build on the local landscape character and ecology to create distinctive and ecologically valuable places.

2.6 The new park **must** include:

- A pavilion to attract visitors and encourage activity.
- Spaces designed to engage people with landscape, nature and healthy eating opportunities;
- Spaces that are accessible to people of all ages and all genders;
- A sensitive lighting strategy to promote safety whilst preserving the landscape character and ecology.

Suitable Alternative Natural Green space (SANG) requirements

The provision of SANG is required to avoid and/or mitigate recreational pressure on designated sites.

- 2.7 The design and delivery must follow best practice guidance and case studies and the principles set out in Natural England's SANG guidance and Part 3.2 of the EFDC Green Infrastructure Strategy.
- 2.8 The SANG **must** include:
- Good pedestrian connections with homes and other open spaces and walking routes
- Attractive walking routes with open sight lines and appropriately surfaced paths.
- Access for dog walking with off-lead areas
- Seating, litter and dog waste bins
- Signage and interpretation
- Ongoing landscape management.

Sports pitches requirements

- 2.9 Community sports grounds **must** be designed in line with Sport England and sports governing body recommendations.
- 2.10 Options for shared facilities at the schools must be explored.

2.11 Sports pitches **must** include:

- Ample cycle parking provision and an appropriate level of car parking.
- A sports pavilion, including publicly accessible toilets, changing, refreshment and storage facilities.
- Detailed boundary treatments and access points including screening of the pitches from the naturalistic SANG.

Allotments and food growing requirements

Productive landscapes will serve social and educational functions that benefit community development and promote a circular economy and healthy lifestyles.

- 2.12 There **must** be informal local growing hubs provided within the main development area, located along key active travel routes and close to schools and community buildings (see stewardship framework, section 01 for indicative locations).
- 2.13 The new community must be involved in helping to shape allotments and growing hubs.
- 2.14 Food growing spaces **must** include:
- Water for irrigation, sustainably supplied,
- Storage for tools etc,
- Seating and shelter inc trees and structures,
- Uncovered cycle parking,
- Appropriate lighting for safety,
- Greenhouses and raised planting beds.





Shared productive landscapes create space for social connections.

Greenway requirements

The greenway provides a direct nature-rich green Green fingers and nodes support SuDS and ecology route for safe and attractive active travel across the neighbourhood and to the local centre and new schools.

2.15 The greenway **must** include:

- Semi-natural greenspaces, SuDS and tree planting as well as organic and natural play equipment.
- Planting schemes that are coherent but vary . according to the character area that the greenway is passing through.
- Trees positioned to create both sunny and shaded spaces for activities, with consideration of the safety of active travel route once trees are mature.

See Section '03: Movement' and 'Section 04: Public Space' for further greenway and green finger requirements.

Green finger/ node requirements

networks. They also provide green views to homes and easily accessible safe, green spaces.

2.16 Green fingers/ nodes must include:

- Seasonally changing, semi-naturalistic landscapes including grassland and wildflower meadows with diversity of grass length for interest and biodiversity.
- Varying widths and character with a minimum width of 5m of soft landscape or SuDS 2.19 The site-wide landscape and public realm throughout, widening to accommodate green nodes for functions such as play, socialising and community growing.
- Seating, play and uncovered cycle parking.
- Lighting designed to promote safety whilst allowing for ecology and wildlife to thrive.

Street trees and greenery requirements

Street trees and greenery will contribute to biodiversity, sustainability, micro-climate of streets, street character and placemaking and outlook for homes.

- 2.17 To provide equitable benefits of tree planting, every home **should** have a view of at least three decent-sized trees in the public realm.
- 2.18 Approximately 25% of trees should be semimature from the outset.
- strategy **must** include a site-wide tree strategy that has:
- Species selection that supports street hierarchy and character, visual connectivity and climate resilience.
- Diverse species selection, with no one species making up more than 10% of the overall population.



Cycling through a green spine at Vally Gardens, Brighton.



Central green at Lovedon Fields, Hampshire. John Pardey Architects.



'Green finger' example at Eddington, Alison Brooks and Pollard Thomas Edwards

Consideration of canopy heights to avoid creating an obstruction to street users and to create a sense of visual openness to support perceptions of safety.

Coordination with SuDS and street infrastructure such as footways, with measures for protecting roots against compaction.

Strategy for passive solar design in tree placement e.g. trees on the north side of a street to shade south-facing facades and prevent overheating in summer. Similarly, consideration of tree placement when used to provide shade for seating or activity.

Post-installation care and funding plan aligned with the wider stewardship framework.

Use of dual-function street furniture e.g. benches with planters, green roofs to bin/bike enclosures).

Street trees in character with the street, Poundbury, ESHA Architects

Wetland park edge requirements

The wetland parks on the northern part of the site will be calm, attractive and characterful settings that plays a significant role in ecology, biodiversity and SuDS.

- 2.20 The geometry of park edge buildings and any associated hard infrastructure **must** relate positively to the geometry of the landscape and topography.
- 2.21 The wetland parks **must** include:
- Some basins that take the form of ponds, with water held permanently below the outfall level to provide a habitat for wetland ecology and a landscape feature.
- Multi-functional uses such as play or recreation where basins are designed to normally be dry.
- Biodiverse wetland meadows with native planting and flowering plants suited to frequent saturation.
- Footpaths and informal cycle ways, seating areas, incidental play, stepping stones and boardwalks to realise the amenity and education value of the wetland park.
- Footpaths that respond to connections through to the amenity area north of the site.
- Trees dotted alone or in small clusters around the wetland park, to enhance the tranquil setting without obstructing connectivity or views from adjacent houses.



Space for ecology enhancing planting and play around wetlands at Barton Park, Oxford. Alison Brooks and Pollard Thomas Edwards.

Edges and existing hedgerow requirements

- 2.22 All edges and retained hedgerows must 2.29 Development must be set back at least prioritise ecology and habitat connectivity and should not be used as main active travel routes.
- 2.23 Lighting must be sensitively designed and 2.30 The design of the buffer must provide a hedgerows buffered with flower rich grassland to enhance their visual quality and biodiversity.
- 2.24 Planting at edges and hedgerows must be appropriate for the landscape character area and must contribute to connectivity for pollinators 2.31 Active travel routes along woodland edges and other wildlife. A diverse palette of native and non-native trees, shrubs and herbaceous plants should be provided for year-round colour and seasonality. Tree planting could be used to provide vertical structure and enhanced biodiversity.

Ridgeline edge requirements

The ridge forms the highest land point in the District and was is defining landscape feature for Harlow.

- 2.25 Development **must not** extend south of the ridge line, shown as the build-to-line in the mandatory spatial principles in the SMF. The exception to this may be ancillary works in relation to the sports fields, which would need to be sensitively designed.
- 2.26 A new 'wooded horizon' should be created through tree planting to supplement existing planting and create an ecological corridor.
- 2.27 Overlooked active travel connections should be provided to the allotments and pitches to the south.
- 2.28 Boundary treatments to the allotments and pitches **must** be designed to preserve the natural character of the ridgeline and outlook for homes that front it.

Woodland edge requirements

- 25m from the boundary of Marks Bushes and min.10m from other woodland edges.
- transition in character between woodland and domestic setting. Private thresholds and boundary treatments **must** be designed as part of this transition.
- **must** be overlooked by homes, with sensitive lighting design to consider ecology.
- 2.32 Where it would not cause harm to ecology or nature, opportunities to lift canopies and clear scrub on the edge of woodlands should be explored in line with the EFDC Green Infrastructure Strategy principles of enhancing, revealing and engaging with the landscape.
- 2.33 Opportunities for wayfinding and art and the facilitation of natural play and activity should be explored to enhance and activate woodland edges and help deliver multifunctional spaces.

Rye Hill Road edge requirements

This edge will have a similar feel to the wetland park edge owing to the band of swales that runs along it.

- 2.34 Rye Hill road frontage should be robust in response to the location at one of the key gateways to the site and the proximity to Rye Hill Road.
- 2.35 Tree planting should be focused at the boundary with Rye Hill Road and amenity footpaths and cycleways should be well overlooked by new homes.



Car free green edge, Leeds Climate Innovation District, White Arkitekter.

SuDS strategy

SuDS will contribute to a healthy, high-quality and distinctive place, responding to the climate emergency through a future-proofing strategy.

The site-wide SuDS strategy will utilise the topography of the site to help control the quantity and quality of surface water runoff, alleviating flood risk and addressing issues of runoff from the site currently impacting neighbouring residents.



SuDS to shape street character, BO01, Malmo, Sweden.



Biodiverse and attractive SuDS planting, QE Olympic Park.



Multifunctional green infrastructure, Boszoom, Netherlands. Photo: Nanda Sluijsmans.

SuDS infrastructure requirements

- 2.36 A site-wide SuDS strategy **must** be prepared as part of a coordinated landscape and public realm strategy, following the hierarchy for nature-based solutions set out in the Essex SuDS design guide. This must be coordinated with topography, ecology, landscape and placemaking.
- 2.37 SuDS features should be above ground where possible and visible in the public realm as positive features to aid placemaking. Opportunities for integrating SuDS with activities such as play, recreation, food growing, biodiversity, education and improved outlook **must** be explored and incorporated where possible.
- 2.38 Swales must be used along green fingers and the greenway. Rain gardens should be used on Latton Avenue and secondary streets and opportunities for rain gardens or SuDS tree pits on other streets should also be maximised.
- 2.39 Ponds and swales must be designed with shallow slopes no steeper than I in 3, and dense planting around the edges of permanent water to avoid the need for barriers and reduce maintenance.
- 2.40 Hillside wetland parks should incorporate swales, channels, rain gardens, permeable paving and wetland areas interspersed with activity areas such as seating, picnic areas, play and food growing.
- 2.41 On-plot SuDS must be provided to help manage individual building water runoff and add to the overall attenuation volume of the development.
- 2.42 Surface water discharge rates must be equivalent to the I in I Greenfield rate for all events up to the I in 100 years plus climate change.

02/ Nature Water management

Illustrative SuDS framework plan showing key components and routes



Existing tree belt/ hedgerow/ field boundary Sustainable transport corridor New green open space/ recreation Woods and tree planting Greenway Green links inc north-south green corridors Street greenery inc biodiversity planting and street trees SuDS attenuation basins/ wetland ponds Primary blue corridor (swales) •Secondary blue corridor (rain gardens) • • Hillside wetland parks N.B

Existing green space/ recreation

Key strategies for active and sustainable travel

- Promote a culture of sustainable ways of getting around through design at every scale.
- Provide safe and attractive cycling and walking routes throughout a street network that is easy to navigate.
- Design streets and open spaces with a positive character that responds to function and hierarchy.
- Offer a range of visible, convenient and appealing sustainable movement options for journeys within the new neighbourhood and key destinations in the wider area, including a sustainable transport corridor into Harlow.

The Harlow and Gilston Garden Town has an overall target of 60% of journeys to be made by non-car modes. This will provide benefits at every scale, including:

- healthy, safe streets for all
- vibrant public realm
- connected communities,
- economic benefits for local businesses.
- reduced congestion on surrounding roads,
- reduced environmental impact and
- resilience to resource scarcity and fuel poverty

See also: Nature Public Spaces – Multi-functional streets Built Form – Block structure EFDC Local Plan Policy SP2 and SP3 **HGGT** Vision HGGT Transport Strategy HGGT Measures to achieve mode share target Building Sustainable Transport into New Dev, DfT Manual for Streets, DfT Active Design Guidance, Sport England Draft parking standards for Garden Communities, ECC

Where sustainable movement is visible and convenient it becomes an embedded part of the culture. Achieving this requires bold planning and an ambitious, holistic approach to make active and sustainable movement the default choice for everyday journeys.

Whilst this strategic design code focuses on hard infrastructure elements at the scale of streets, homes and buildings, future applications must address the wider connectivity and the 'soft' elements, employing a comprehensive programme to embed sustainable movement culture.



Epping Forest District Council

Active travel network requirements

- 3.1 The active travel network **must** provide direct, accessible and convenient links to surrounding areas and key destinations including signposting, upgrades and new routes as required.
- 3.2 Streets **must** be clearly differentiated through scale, enclosure and character, providing a choice of safe and attractive active travel routes.
- 3.3 The street network **must** incorporate designated quiet active travel routes to key destinations that are car-free or low car through filtered permeability, well-lit and overlooked on both sides.
- 3.4 All primary and quiet active travel routes must have gradients no steeper than 1:20 for any part of them. This may require alternative meandering routes with shallower gradients over longer distances where site topography is most severe. Such routes must be well integrated and attractive.
- 3.5 Continuous and level footways should be provided on both sides of primary and quiet active travel routes and at least one side of other streets except where a shared surface approach is used.
- 3.6 Street design must include measures to prevent ad-hoc parking that impedes footways and cycleways.
- 3.7 Sustainable transport infrastructure must be supported by services such as demandresponsive transport, car-clubs and reliable real-time travel information.

Illustrative site-wide strategy for active travel



Strategic Design Code / Latton Priory / JULY 2024

Sustainable transport infrastructure

The delivery of sustainable transport infrastructure will be critical to the success and sustainability of the new community at Latton Priory.

A Sustainable Transport Corridor (STC) will provide cycling, walking and bus rapid transit conveniently from Harlow Town Centre to the new local centre. STC requirements are described in 'HGGT STC placeshaping principles' and should be referenced in proposals.

Mobility hubs will provide a choice of sustainable transport modes and make it easy to switch between those modes. Users will arrive by walking, wheeling or cycling and either use one of the facilities or transfer modes as shown on the diagram across.

A main community mobility hub will be located in the local centre. This will be supplemented by smaller 'mini mobility hubs' at key nodes.

General mobility hub requirements

- 3.8 Mobility hubs must be accessible and easy to navigate through good design.
- 3.9 Mini mobility hubs must include;
 - Waiting environment and real time information, where the hub is co-located with a bus stop.
 - Cycle parking.
 - Car club vehicle(s) in on-street marked bays.
 - A meeting point including seating and enhanced public realm.

Community mobility hub requirements

- 3.10 The mobility hub **must** contribute positively to the public realm through high-quality, distinctive architecture and a focus on community placemaking.
- 3.11 The mobility hub and STC/ Latton Avenue junction **must** conform with the principles shown opposite, including:
 - Bus integration including bus interchange.
 - Neighbourhood car club.
 - Cycle infrastructure for short and long distance journeys including electric bike and cargo bike hire.
 - Car park integration with EV charging.
 - Secure and covered cycle parking, accessible 24/7.
 - A café for activity and natural surveillance.
 - WC facilities
 - Cycle maintenance.
 - Delivery hub for parcel drop off and collection.
 - Real time mobility information including smart screens and QR code app downloads
 - · 'Secure by Design' principles balanced with placemaking and inclusivity.
- 3.12 Other functions **must** be established through community and stakeholder engagement.
- 3.13 Operation and long-term management of the community mobility hub must be considered and designed for at the early stages.





Community mobility hub plan and STC section

Mobility hub principles diagram

03/ Movement Site-wide sustainable movement



Public transport will be a key component of the sustainable transport strategy and any future planning application must include details of proposed bus services, including bus rapid transit, demand responsive transport and associated infrastructure.

Whilst sustainable movement will be the priority, cars will be necessary for some journeys, and access needed for deliveries and servicing. Vehicle movement and parking should be accommodated in a way that encourages more sustainable modes of travel, limits the impact of vehicles on streets and open spaces and can adapt as transport technology evolves and moves away from private car ownership.

In order to design streets and spaces around people rather than cars and to minimise the hard infrastructure associated with vehicular access, vehicular movement must be planned strategically in order to make efficient use of streets whilst allowing for homes to be serviced. The site-wide strategy for vehicular movement shown opposite illustrates how vehicle access should be balanced with car-free frontages, particularly around green spaces and play spaces within the development.



Public transport and active travel priority

9	
ع ۱ ۱	
3.17 S	
5	
F	
3.18	
t	
Ņ	
3.19	
C	
3.20	
(
C	
3.21	
5. <u>2</u> 1	
3.22	
5.22 f	
I	
ł	
3.23	
2	
a (
3.24	
t	

Vehicular movement strategy requirements

- 3.14 Public transport **must** be integrated to provide a direct connection to Harlow via the Sustainable Transport corridor and to Epping via the new B1393 connector. All homes **must** be within 800m of a bus rapid transit stop.
- 3.15 A meandering central route **must** be the single through-route for vehicles, with vehicular loops providing service and access to small low-traffic neighbourhoods with filtered permeability to prevent through-routes for vehicles.
- 3.16 Vehicular movement **should** follow a hierarchy so that spur streets and parking court access routes do not connect directly to primary or secondary vehicular routes unless unavoidable.
- 17 Vehicular access should be limited to three sides of any development block or two sides plus a rear parking court.
- 18 Key green routes including the greenway and the north-south green fingers must not have vehicle access on both sides at any point.
- 19 There must be no more than three vehicular crossings over the greenway.
- 20 Vehicular access **must not** be provided on either side of the greenway through the local centre including to the school frontages.
- 21 Vehicular access **must not** be provided on the community park frontages, except for STC.
- 22 Green nodes and play spaces **must** have carfree aspects on a minimum of two sides. The need for crossing vehicular streets between housing and play spaces **should** be minimised.
- 23 Neighbourhood nodes should have car free aspects on a minimum of two sides to maximise overlooking and to allow space for social activity.
- 24 Speed limits **must not** exceed 20mph throughout. Lower speeds **must** be encouraged through street design.
Illustrative site-wide strategy for vehicular movement



STC route shown indicatively

The active travel strategy combined with the vehicular movement strategy form the basis of the street network, as shown opposite. The street network is well connected, allowing for access and servicing but without allowing vehicles to dominate the network. Modal filters are used to provide social, safe streets without the need for cul-de-sacs that limit active travel permeability.

Key street types	Priority of modes	Adoptable standards	
SI Latton Avenue inc local high street	 Primary active travel route Bus route Primary vehicular route, except on STC 	Yes	
S2 Local streets	Primary active travel routeSecondary vehicular route	Yes	
S3a Neighbourhood streets on key green edge inc greenway	Tertiary vehicular route and service loop	Preferably	
S3b Neighbourhood streets	 Non-designated active travel route Tertiary vehicular route and service loop 	Preferably	
S4a Spur streets (with modal filters) on key green edge inc greenway	 Tertiary vehicular route – no through route Limited service access 	No	
S4b Spur streets (with modal filters)	 Non-designated active travel route Tertiary vehicular route - no through route Limited service access 	No	
S5 Greenway	Primary active travel routeNo vehicular movement	TBD	
S6 Car-free play streets	 Primary or non-designated active travel route No vehicular movement 	No	
S7 Car-free interface with green infrastructure, nodes and schools	 Active travel mainly for residential access No vehicular movement 	TBD	

Illustrative site-wide street strategy



Car parking will have a significant impact on the character and vibrancy of streets and spaces as well as the extent to which active and sustainable modes of transport are encouraged. Car parking also needs to be adaptable so that parking spaces can be used in a different way should car ownership fall in the future.

Parking quantum will be assessed at application stage based on technical studies, accounting for proposed active and sustainable travel measures and proposed parking controls. This design code sets out the requirements for how that parking is configured.

On-street car parking allows continuous footways without vehicle crossovers, unallocated parking for efficient land use, adaptability and better overlooking of public realm through proximity of homes. It can also provide parking for nearby homes on car-free streets. .

The site-wide car parking requirements are intended to maximise the benefit of on-street parking in conjunction with the active travel and green infrastructure / play strategy while providing a variety of parking types across the site, including some on-plot parking.

Site-wide car parking requirements

Latton Avenue and local streets

3.25 Parking must be on-street, providing continuous level footways on both sides.

Local centre

3.26 Any parking along the high-street/ Latton Avenue **must** be on-street or to the rear of blocks.

Neighbourhood streets on ridgeline edge, woodland edge, wetland park edge

- 3.32 Parking should be on-street to maximise 3.27 Parking **should** be on-plot and located behind perceived overlooking and natural surveillance. the building line in order to minimise the distance between homes and the green space. Streets alongside greenway
- 3.28 Parking for visitors or residents could be 3.33 Parking should be on-plot. The on-plot incorporated on the opposite side of the street, parking **should** be located behind the building only for the length of the on-plot parking. This line to maximise proximity between homes and must be sensitively designed in clusters of no greenway. more than four spaces and **must not** block Destinations green vistas.

Spur streets on ridgeline edge, woodland edge, wetland park edge

3.29 Parking should be on-street, on built side only.

Residential streets (homes both sides) and key edges (Dorrington, Riddings, existing G&T etc)

3.30 On-plot parking **must not** be used on both sides of the street.

Car-free frontages

3.31 Parking needs **must** be met by rear parking courts or street parking on adjacent streets.

Frontages to strategic play spaces

3.34 Destinations such as the SANG and sports pitches must have sensitively integrated appropriate levels of parking, with shared use parking where possible.

Illustrative site-wide car parking strategy







Well integrated enclosed car port with potential for future conversion to living space. Loveden Fields, Hampshire by John Pardey Associates.

On-plot parking requirements

- 3.35 Cycle parking **must** be accessible and more convenient than any on-plot or off-plot car parking. This generally means locating secure cycle parking enclosures at the front entrance or side of properties. Care must be taken not to impact pedestrian visibility splays.
- 3.36 Where convenient rear access is available e.g. via a parking court, cycle parking enclosures **could** be provided in the rear garden instead of at the front.
- 3.37 Cycle parking enclosures **should** include space for cycling accessories, be sized to accommodate a variety of cycle sizes and include direct mains power for the battery charging of electric bikes.
- 3.38 Driveways to the sides of houses **must** be long enough to allow all of the car length to be behind the building line whilst providing cycle parking in a more convenient location.
- 3.39 Driveways **must** be a minimum of 3m wide and, on SI – S3 streets, provide a 1.5m x 1.5m pedestrian vision splay. Where private frontages/ thresholds are less than 2m, this will require widening of driveways / adjustments to vertical features that limit visibility to accommodate the splay.
- 3.40 All houses with on-plot parking **must** have a dedicated (Electric Vehicle) EV charging point.





On-street parking integrated with soft landscaping and pedestrian crossing points. Goldsmith Street, Norwich by Mikhail Riches Architects.

On-street parking requirements

3.41 Secure and overlooked cycle parking **must** be provided in a location that is closer than car parking spaces or drop off bays to the entrances of schools, shops and other facilities in accordance with LTN 1/20.

3.42 Visitor and staff cycle parking **must** also be provided as Sheffield style cycle stands in the public realm and within dedicated facilities at mobility hubs.

3.43 On-street vehicle spaces **must** be in designated bays and part of a Controlled Parking Zone or Restricted Zone, forming part of the adopted highway network. Where a street is unadopted, any parking **should** be allocated or privately managed.

3.44 Parallel parking bays on Latton Avenue **should** be 6m long and 2.5m wide, and on other streets where doors can open into the street or footway, **should** be 6m long and 2m wide.

3.45 Parallel bays that are constrained along one edge by a vertical feature over 0.9m high **should** be wider and 2.7m is recommended.

3.46 Where parallel bays on S2-S4 streets do not adjoin a footway, but are unconstrained above 0.9m, their width **should** be increased to 2.5m.

3.47 Runs of parking bays **must** be broken up by trees and planting.

3.48 Parking bays **should** be located at least 6 metres from minor junctions and **should not** impact pedestrian and cyclist visibility at crossing points.

3.49 All parking spaces **must** have access to on-street EV chargers.

03/ Movement **Parking design**





Attractive and functional on-street parking court at Loveden Fields, Hampshire by John Pardey Associates and BD Landscape Architects.

Parking court requirements

- 3.50 Front parking courts should only be used on S4 spur streets (see Multi-functional streets, Section 04: Public Space), with parking in small clusters of 2 or 3 bays set back from the primary building line.
- 3.51 Front parking courts must be designed as attractive public realm with street furniture and soft landscaping, whilst accommodating turning • heads.
- 3.52 Rear parking courts **must** only be used where necessary to accommodate parking for blocks with multiple car-free frontages.
- 3.53 Access to rear parking courts must be . overlooked by properties on the opposite side of the street and **must not** be located directly opposite another rear parking court access.
- 3.54 Parking courts should contain no more than twelve spaces and should include green infrastructure, with planting/ trees breaking up every four spaces.
- 3.55 Parking courts should be well overlooked.
- 3.56 Parking courts should be designed to encourage front door access to homes and avoid excessive use of rear gates.

Parking barns

- 3.57 Parking barns **should** be used for extra spaces A parking barn is a structure that provides covered, semi-outdoor parking spaces for vehicles, typically where homes require more than one space or cars, vans or motorcycles. They have the following require parking for oversized vehicles such as key benefits: vans.
- they locate parking remote from the home 3.58 Parking barns **should** be located within 400m and therefore discourage car use over more (5 min walk) of the homes served. sustainable modes of travel.
- they reduce the requirement for car parking properties via permits. in the public realm, thereby reducing car 3.60 Parking barns should typically start at around dominance on streets and open spaces. 50 spaces over two levels (approx. 36×40 m).
- they can more easily accommodate larger 3.61 Electric vehicle charging must be incorporated vehicles such as vans. into all vehicle parking spaces.
- they provide protection from the weather, 3.62 Parking barn entrances must be overlooked helping to preserve the condition of vehicles. by surrounding active frontage to maximise they offer future flexibility if they are designed security. Cladding and fenestration should be to be adapted or replaced with other uses permeable to allow sight into and out of the should car ownership fall in the future. structure.



Example of remote parking barn in Zutphen, Netherlands by MoederscheimMoonen Architects.

Parking barn requirements

3.59 Spaces could be allocated to specific

- 3.63 Parking barns must be well designed to contribute positively to the public realm.
- 3.64 Options for integrating sustainability and biodiversity measures should be explored and implemented where feasible. These could include PV panels, rainwater harvesting and green walls.
- 3.65 Parking barns could be combined with mobility hubs, with forecourts providing EV charging points, car club parking, secure cycle parking and delivery vehicle space.
- 3.66 Car barns should adjoin residential blocks to minimise lengths of inactive frontage.
- 3.67 Security should be well considered including good lighting, motion-detection lighting and CCTV as appropriate. The facility should achieve British Association Parking 'Park Mark' accreditation.

Fire and waste and recycling access strategy

A servicing strategy will ensure that all buildings can be serviced without requiring all streets to be of a scale and character to accommodate servicing vehicles. This relies on considered block dimensions and street design. Where there are potential conflicts between the technical servicing guidance and placemaking requirements, this should be resolved with the local authority and relevant body.

Provision of convenient bin storage will be most challenging on terraced typologies with shallow front threshold spaces and no access to the rear, however there are high-quality precedents where an enclosure is designed as part of the built form and helps to emphasise the rhythm of the houses.

The site-wide servicing strategy will also need to address emergency and refuse and recycling collection from the local centre facilities and new schools, through consultation with the relevant authorities and end users, including Essex County Council as education authority.

Current standards for refuse and recycling:

EFDC Waste and Recycling provisions for new residential and business developments. Good practice guide for developers.

- Refuse collection will be made only from those dwellings within 25m of an adopted road.
- Storage areas for waste containers should be sited so that the distance householders are required to carry refuse does not usually exceed 25m (excluding vertical distance).

Essex Design Guide: Refuse Collection:

- Refuse collection will be made only from those dwellings within 25m of an adopted road.
- In other cases, it is necessary to provide a shared bin-collection point screened by an above eyelevel wall. This should be located within 25m of an adopted road.

Waste and recycling requirements

- 3.68 A waste and recycling strategy **must** be 3.74 Where collection is from the rear of a dwelling, provided that provides details of service access a suitable bin enclosure **must** be provided in and bin storage for individual homes, flats and the rear garden and the parking court must non-residential premises to avoid 'bin blight'. provide adequate turning circles and guarding to protect parked vehicles from damage.
- 3.69 Latton Ave, local streets and neighbourhood streets should be used as service loops to 3.75 Communal underground storage or bin maintain the street network strategy as shown collection points should be provided where on the diagram opposite, including car-free any home is further than 25m* from an adopted road with refuse access. Any communal bin frontages. point **should** be well designed as part of the 3.70 Waste and recycling collection vehicles should street scene and **should not** service more than be able to proceed mainly in a forward motion. ten designated dwellings.
- Any turning heads must be well integrated into the street design.
- 3.71 Communal bin stores for flats and nonresidential premises **must** be integrated into the main building footprint with rear access to avoid blank frontages. These **must** be easily accessible by residents under shelter from a communal door but **must not** be accessed 3.77 Bin enclosures **must** be designed to directly from inside the block.
- 3.72 Individual households should have welldesigned bin enclosures that are part of the street scene.
- 3.73 For detached/ semi-detached homes without rear access for collection, the bin enclosure **should** be located behind the building line.



Considered bin enclosure design for terraced housing. Riverside Rd housing, Watford by Bell Phillips.

- 3.76 The feasibility of a site-wide underground vacuum and / or waste storage system should be explored at an early stage to reduce onstreet bin clutter. If this is not found to be feasible at the outset, the layout should allow for ease of future implementation.
 - accommodate all bins provided by the Council. Road-end collection points **must** be designed to accommodate all the bins from each household served by that collection point on any given bin collection day.

*Based on Essex Design Guide. Acceptable distance for operatives to drag bins to be confirmed with relevant authority.



Underground refuse and recycling system, Eddington, Cambridge.

Illustrative site-wide refuse collection strategy



Refuse collection strategy

- Sustainable Transport Corridor (Bus Rapid Transit/ walking/ cycling) Greenway
- Spur streets use of these for refuse access must be minimised.
- Rear parking court refuse collection point
- ------ Homes with rear refuse collection
- Communal refuse storage or enclosure within 10m of an adopted road
- Δοργογ 25m travel distance

Key strategies for uplifting and safe streets and spaces	
• Design the public realm around people foremost, with a human scale and promoting activity.	
• Incorporate overlooking, mixed land uses, generous provision for natural play and a range of info and formal leisure activities to provide opportunities for all.	nformal
• Create a legacy for future generations through the exemplary open space and a sense of owner	nership.
• Make art, innovative design and green infrastructure part of everyday life.	
• Use technology and digital connectivity to allow social, cultural, education and business activi buildings and open spaces to meet current and future needs.	ivity in
ublic space includes open spaces and the network	
of streets that provide the setting for daily life. A	
nigh-quality public realm will prioritise people and nature, whilst accommodating vehicle movement	
efficiently. A clear hierarchy to streets and spaces	
vill help people to navigate the public realm and vill also provide the appropriate variety of spaces	
or a range of social and leisure opportunities,	
rom neighbourly chats to cultural events in the community plaza.	
	180
See also: Nature	AT SO
Movement - Active travel network	TO X
EFDC Local Plan Policy SP2, SP4, DM5 and DM9	
EFDC Green Infrastructure Strategy	
HGGT Vision and Design Guide	
Harlow Sculpture Town	

Make Space for Girls Guidance

Essex Design Guide - Women and Girls' Safety in the public realm

Well integrated art, seating and lighting at Timekeepers Square, Salford by Buttress Architects.

ublic space requirements

- I Detailed design codes for site-wide coordinated landscape and public realm proposals **must** be endorsed for the whole masterplan area concurrently or in advance of, any full planning application or Reserved Matters Application.
- 2 High quality art **must** be used to enrich the public realm, aid character, wayfinding and uplifting moments. A site-wide arts strategy **must** be developed with the community and with oversight from the Harlow Arts trust.
- 3 The function of open spaces and their boundaries and the public, private or shared nature of them **must** be clearly defined.
- 4 Lighting **must** be provided on all streets and key open spaces, of a type appropriate to the character and function of the space.
- 5 Seating design **must** be high quality, of appropriate character and vary in design to accommodate different users including shading devices.
- 6 Public toilets and bins (litter, recycling and dog waste) **should** be provided at the local centre, the SANG and the Community Park as a minimum.
- 7 Ad-hoc parking **must** be discouraged through design measures such as street layout, material choice, planting and street furniture.
- 8 Underground utilities and service chambers **must** be planned in dedicated zones away from tree root zones and other conflicts.
- 9 There **should** be high-speed digital connectivity, including full fibre and 5G to all parts of the public realm network, with flexibility for technology upgrades in the future. Infrastructure **should** be considered at an early stage and designed sensitively as part of the public realm.

Illustrative site-wide public space network



SI Latton Avenue

Latton Avenue is the primary vehicular and cycle route through the new neighbourhood, providing safe movement and access to a diverse range of land uses; its design will be a key driver for the character of the masterplan area.



Avenue with green verges/ parking both sides. Great Kneighton, Cambridge by Proctor and Matthews.



Parking with street trees, cycle and footpaths. Knights Park, Eddington, Cambridge by Pollard Thomas Edwards.

Place requirements

- 4.1 The design of Latton Avenue **must** vary along 4.10 Car parking along Latton Avenue should its length depending on the character of the be on-street in parallel bays. Small clusters of perpendicular on-street bays could be area it is passing through. Character **should** be acceptable in the local centre. varied by changing the mix and design of key street components shown opposite.
- landscape verge zones as shown. 4.2 Latton Avenue should not be wider than 19.75m between private thresholds unless it 4.12 There **must** be no more than four car parking merges with another aspect of public realm or if bays provided continuously between landscape greater width is appropriate in the local centre sections. e.g. for perpendicular car parking on one side.
- 4.3 Seating must be incorporated at regular intervals and at least at every 50m on both sides of the street.
- 4.4 Soft landscape verges and buffers must be at least the full width of the parking spaces, with street trees and SuDS on both sides. Verges must be planted to promote biodiversity and minimise the need for maintenance or mowing.

Movement and access requirements

- 4.5 Kerbed pedestrian zones must be provided on 4.16 Ad-hoc visitor cycle parking **must** be provided both sides of Latton Avenue with continuous within the public realm and level footways.
- 4.6 Cycle lanes **should** be continuous and two-way 4.17 Street drainage **should** be attenuated through on the south side of the street only, separated SuDS such as rain gardens and permeable paving. from vehicular movement. Cycle lanes **must** be high-quality in line with LTN 1/20. 4.18 Lighting should be on columns specified to
- 4.7 Latton Avenue **must** not comprise more than two vehicular lanes at any point. Buses will 4.19 Car chargers and lighting columns must be share the carriageway with private vehicles; placed in line with car parking zones or adjacent stops must be on the carriageway. Bus shelters buffer zones so that footway or cycleway widths **must** be provided without impinging on are not reduced. footway/cycleway widths.
- 4.8 Latton Avenue should provide vehicular access to S2 local streets and S3 neighbourhood streets, but not directly to spur streets or parking courts.
- 4.9 Corner radii leading to side streets should be as tight as possible and no greater than 4m.

Epping Forest District Council

Parking requirements

- 4.11 Car parking **should** be provided within the
- 4.13 Car parking should not terminate the vista at the end of streets that connect on to Latton Avenue.
- 4.14 Allocated car parking should be limited to blue badge spaces and car clubs.
- 4.15 Car parking **should** be controlled by Resident Parking Zones, with strategies to restrict ad-hoc parking and limit the need for excessive signs and lines e.g. parking restricted everywhere except marked bays.

Service requirements

- suit the intended character of the street.
- 4.20 There must be a minimum Im buffer between cycleways and parking bays to allow space for street furniture, car chargers, etc.



- Drainage/ SuDS zone

S2 Local streets

Local streets are primarily residential in nature, serving pedestrians, cyclists and private vehicles but not buses. They may also have some nonresidential uses, such as small businesses, schools or community facilities.



Local Street example at Goldsmith Street. Norwich. Mikhail **Riches Architects.**



Local Street example at Trent Basin, Nottingham. Marsh Grochowski and URBED.

Place requirements

- 4.21 Local streets should generally be no wider 4.29 Parking along local streets should be onthan 13.5m between private thresholds unless street in parallel bays within the landscape they merge with another aspect of public realm verge zones, as shown opposite. e.g. green finger.
- 4.22 Local streets must not incorporate more than two vehicular lanes at any point.
- 4.23 Space for seating and social activity must be 4.31 Parking should not terminate the vista at the incorporated at regular intervals and at least at end of streets that connect on to local streets. every 50m along the length of the street.
- 4.24 Soft landscape verges and buffers must be to blue badge spaces and car clubs. at least the full width of the parking spaces. 4.33 Parking should be controlled by Resident These must incorporate street trees and SuDS Parking Zones, with strategies to restrict ad-hoc on both sides. Verges must be planted to parking and limit the need for excessive signs promote biodiversity and minimise the need for and lines e.g. parking restricted everywhere maintenance or mowing. except marked bays.

Movement and access requirements

- 4.25 Kerbed pedestrian zones must be provided on both sides of local streets with continuous and level footways.
- 4.35 Street drainage **should** be attenuated through 4.26 Cycling should be on carriageway if it is rain gardens and permeable paving. shown that the volume of traffic is low enough 4.36 Lighting **must** be provided to all local streets for this to be achieved safely in line with LTN on columns specified to suit the street character. I/20 table 4.1.
- 4.37 Car chargers and lighting columns must be 4.27 Local streets **should** provide vehicular access placed in line with car parking zones so that between Latton Avenue and neighbourhood footway or cycleway widths are not reduced. streets, but not directly to spur streets or parking courts.
- 4.28 Corner radii leading to side streets (S3) should be as tight as possible and no greater than 4m.

Parking requirements

- 4.30 There **must** be no more than three parking bays provided continuously between landscape sections.
- 4.32 Allocated on-street parking should be limited

4.34 Ad-hoc visitor cycle parking **must** be provided within the public realm

Service requirements



- Pedestrian / cycle priority crossing
- Shared space/ informal crossings

S3 Neighbourhood streets

Neighbourhood streets will make up the greatest length of the street network, providing access to homes and loops for refuse and emergency access. Neighbourhood streets will have a quiet, residential character and a less structured layout than Latton Avenue and local streets. They provide a safe and sociable environment for residents, with low traffic levels and low speeds.



Neighbourhood Street example at Great Kneighton, Cambridge. Procter and Matthews Architects.



Neighbourhood Street example at Rennes, France.

Place requirements

- 4.38 Neighbourhood streets **should** be no wider 4.47 Parking along neighbourhood streets should than 9.3m between private thresholds unless be on-street or on-plot in accordance with the site-wide car parking strategy. merged with another aspect of public realm.
- 4.39 Informal space for social activity should be 4.48 On-street parking **must** be provided within the landscape verge zones as shown. included in the layout. On primary walking routes, this **should** include seating.
- 4.40 Soft landscape verges and buffers must be at least the width of the parking and incorporate street trees and SuDS on at least one side. Verges must be planted to promote biodiversity and minimise the need for maintenance or mowing.
- 4.41 Where the carriageway is directly adjacent a private threshold space, a narrow buffer should be provided between the two.

Movement and access requirements

- 4.42 Neighbourhood streets should be level-4.52 Ad-hoc visitor cycle parking should be surface with a change of material for pedestrian provided within the public realm footways and shared-surface crossing zones to **S**ervice requirements indicate pedestrian priority. Kerbs should be 4.53 Street drainage **should** be attenuated through detectable by people with impaired vision. rain gardens and permeable paving or via a flush channel at the carriageway edge.
- 4.43 Low speeds must be encouraged through narrowing of the carriageway to one lane with landscape and parking. At single-lane sections a cyclist **must** be able to pass a car comfortably.
- 4.44 Single-lane sections should not exceed 26m in length. Minimum distance between staggered narrow sections should be at least 10m and offset of narrow sections from junctions should be at least 15m and greater if required.
- 4.45 Corner radii leading to spur streets (S4) or parking courts **should** be as tight as possible and no greater than 3m. Where service vehicle access is not required, corner radii may be less than Im to prioritise pedestrian crossing.
- 4.46 Internal radii on corners should be 2.5m-4m and as tight as possible, . If service vehicle size and turning radii necessitates, localised widening of the carriageway could be implemented.

Parking requirements

- 4.49 There **must** be no more than three parking bays provided continuously between landscape sections.
- 4.50 Allocated parking should be limited to onplot parking and on-street blue badge spaces.
- 4.51 Parking should be controlled by Resident Parking Zones, with strategies to restrict ad-hoc parking and limit the need for excessive signs and lines e.g. parking restricted everywhere except marked bays.

- 4.54 Lighting **must** be provided on columns where neighbourhood streets form part of the primary active travel network. Elsewhere, the need for lighting **must** be assessed to provide safety, balanced with the needs of ecology.
- 4.55 Car chargers and lighting columns must be placed in line with car parking zones so that footway widths are not reduced.



- Pedestrian / cycle priority crossing
- Shared space/ informal crossings

S4 Spur streets with modal filters

Spur streets have an ultra-low traffic residential character with a human scale and a strong sense of place. Spur streets have modal filters at one end to prevent through-movement of vehicles. Service vehicle access may or may not be required, however shared surface principles should be used to provide an informal and social environment.



Spur street example at Great Kneighton, Cambridge.



Spur street informal space example at the Avenue, Saffron Walden by Pollard Thomas Edwards.

Place requirements

- 4.56 Spur streets should generally be no wider 4.64 Parking should be on-street or on-plot in than 7.1m between private thresholds unless accordance with the site-wide car parking merged with another aspect of public realm. strategy. Spur streets **should** be wider at their ends to 4.65 There **must** be no more than two on-street facilitate vehicle turning alongside integrated parking bays together. street parking and landscape.
- 4.57 Informal space for social activity including seating and informal play should be included, particularly at the wider sections at the ends.
- 4.58 Small soft landscape areas must be provided as shown opposite. These **should** incorporate street trees at the wider sections of street. except marked bays. Landscape areas **must** be planted to promote 4.68 Ad-hoc visitor cycle parking **could** be provided biodiversity and minimise the need for within the public realm maintenance or mowing.
- 4.59 Where the carriageway or car parking is directly adjacent to a private threshold space, 4.69 Street drainage **should** be attenuated through a narrow buffer **should** be provided between permeable paving or via a flush channel at the both. carriageway edge or centre.

Movement and access requirements

- 4.60 Spur streets should be level-surface with shared surface designed to indicate pedestrian priority.
- 4.61 Traffic speeds below 10mph must be 4.71 Car chargers and lighting columns must be encouraged through narrowing of the placed in line with car parking zones, or within carriageway to one-lane (with passing places) adjacent buffers, so that pedestrian and vehicle with landscape and parking. routes are not reduced in width.
- 4.62 One-way vehicle working **must** allow a car and pedestrian / cyclist to pass comfortably.
- 4.63 Spur streets **must** provide through access for pedestrians and cyclists but must not allow through access for vehicles. If non-adopted, the street **must** remain publicly accessible and maintained by an appropriate company.

Epping Forest District Council

Parking requirements

- 4.66 Allocated parking should be limited to onplot parking and on-street blue badge spaces.
- 4.67 Parking should be controlled by Resident Parking Zones, with strategies to restrict ad-hoc parking and limit the need for excessive signs and lines e.g. parking restricted everywhere

Service requirements

- 4.70 Lighting **must** be provided on columns where spur streets form part of the primary active travel network. Elsewhere, the need for lighting must be assessed to provide safety, balanced with the needs of ecology.
- 4.72 Refuse servicing and deliveries should take place at the junction with the neighbourhood street where possible. See 'servicing' section.



- Pedestrian / cycle priority crossing

S5 Greenway

The greenway provides a safe and dedicated space for cycling and walking through a natural corridor.

Place requirements:

- 4.73 Landscape, tree planting, SuDS, play, social and recreation spaces **must** be integral to the design. See 'nature' section.
- 4.74 The greenway **should** vary in width, with a min. 20m width between private thresholds and a minimum width of 8m of soft landscape or SuDS throughout. The soft landscape area **should** widen for intensity at key intersections and focal amenity areas such as pocket parks.

Movement and access requirements

- 4.75 A single two-way cycleway and one or two footways **must** be provided through the greenway. These may be adjacent to each other or separated by green infrastructure. They may be straight or slightly meandering to suit the landscape character.
- 4.76 The need for safe and overlooked active travel **must** be considered in the provision and location of the footway(s), considering the location of trees and mature height.
- 4.77 Convenient walking access **must** be provided from the footway(s) to the homes on either side.
- 4.78 Vehicle access **must not** be provided along the greenway but residential and servicing access for vehicles is permitted on one side in accordance with the site-wide movement and car parking strategy. The access street **must** be minimised in width.
- 4.79 Cycle parking **must** be integrated at nodes.

Service requirements

4.80 Low-level lighting **must** be provided along footways and cycleways for safe active travel.









S6 Car-free play streets

Play streets provide safe and sociable spaces for residents and also form a key component of the quiet/ low-car active travel network. They provide an opportunity for smaller scale streets with shade and seating and an attractive outlook for homes.

Place requirements:

- 4.81 The street **should** be generally 8m wide between buildings, widening in areas to provide space for play, interaction, seating and landscape.
- 4.82 Where the distance between building frontages is constant, private frontages / privacy strips **should** vary in depth to provide variety in the width of the public realm.
- 4.83 Small soft landscape areas **must** be provided as shown opposite. These **should** incorporate street trees at the wider sections of street. Landscape areas **must** be planted to promote biodiversity and minimise the need for maintenance or mowing.

Movement and access requirements:

- 4.84 Car-free play streets **should** be level-surface throughout.
- 4.85 Play streets **should** maintain connectivity at both ends for pedestrians and cycle access, with modal filters to prevent vehicle access.

Cycle parking requirements:

4.86 Resident cycle parking **should** be provided in shared cycle storage that is conveniently located and well-designed as part of the streetscene.

Service requirements:

- 4.87 Lighting **must** be provided on columns or bollards where car-free play streets form part of the primary active travel network. Elsewhere, the need for lighting **should** be assessed.
- 4.88 Landscape and SuDS features **should** double up as child-friendly, interactive play and discovery elements.











Principles of junction design

Well designed junctions prioritise walking, encourage lower vehicle speeds and respond to the street hierarchy. Whilst each junction must be designed in detail, including consideration of building footprint at corners, the following pages illustrate key junctions in the street network, particularly along primary active travel routes. Other junctions should be designed similarly.

Requirements for all junctions

- 4.89 All junctions must prioritise pedestrians, then cyclists, then vehicles.
- 4.90 Material selection at junctions and crossings should make the space feel part of the pedestrian/ cycle zone and that vehicles should pass with care.
- 4.91 Particularly where there are level changes for vehicles, materials **must** also be specified with consideration for durability and maintenance.
- 4.92 A variety of crossing types must be provided for pedestrians and cyclists, with the type proposed dependent on location and traffic flow analysis. Crossings could be formal or informal as appropriate.
- 4.93 Formal pedestrian and cycle crossings should generally be non-signalised except where required to provide bus priority at the junction of the STC and Latton Avenue.
- 4.94 Non-signalised formal crossings could include zebra crossings, 'Copenhagen'/ continuous pavement crossings, parallel crossings or cycle priority crossings.
- 4.95 Formal crossings **should** be raised to match the level of the footway or cycleway. Where they are not raised, drop kerbs must be provided.
- 4.96 Informal crossings should be at carriageway level, with suitable dropped kerbs where carriageway and footway levels differ.

lunction I

SI Latton Avenue / S5 Greenway

Latton Avenue and the greenway are the two main arteries. The greenway is crossed by Latton Avenue at two locations; these are the only vehicle crossing points along the greenway.

The greenway will serve as a social and recreational space so it is important that the Latton Avenue junction is sensitively designed, reducing potential for conflict between cars and other modes without appearing that the greenway is being severed.

- 4.97 For pedestrians, a zebra crossing in accordance with LTN2/95 must be provided over Latton Avenue to afford pedestrians maximum priority allowing movement from any of the 4 footways.
- 4.98 For cyclists, a parallel crossing must be provided next to the zebra crossing allowing transfer from the Latton Ave bidirectional cycleway to the greenway in accordance with LTNI/20 Table 10-2.
- 4.99 The crossings **should** be provided on a raised table at footway level to encourage lower traffic speeds and give pedestrians and cyclists a more continuous flow.
- 4.100 The Latton Avenue carriageway width must be narrowed to maximum 5.5m at the crossing to reduce crossing distances, reverting to the standard carriageway width immediately adjacent to the crossing.
- 4.101 Crossing spacing should be at least 200m offset.
- 4.102 Where footways or cycleways along Latton Avenue cross a neighbourhood street associated with the Greenway, then an informal crossing or formal Copenhagen, or cycle priority crossing could be used.





Soft landscape/ SuDS

- Urban realm Buffer/ street furniture zone
- Pedestrian / cycle priority crossing Shared space/ informal crossings Ramp to raised table / crossing \rightarrow Vehicle movement Cycle movement Cycle route transition zone

Junction 2

SI Latton Avenue / green finger

As with the greenway, the green finger is a key active travel route and serves wider place functions including play and recreation. Therefore, there will need to be similar considerations where Latton Avenue crosses a green finger.

- 4.103 On primary active travel routes along green fingers, at crossings, a zebra crossing in accordance with LTN2/95 must be used. For cycles, a parallel crossing must be provided. On quiet routes, informal crossings could be provided instead.
- 4.104 Formal crossings should be provided on a raised table at footway level to encourage lower traffic speeds and give pedestrians and cyclists a more continuous flow.
- 4.105 On raised tables the Latton Avenue carriageway width **must** be narrowed to max 5.5m to reduce crossing distances and revert to the standard carriageway width immediately adjacent to the crossing.
- 4.106 Where an informal crossing point is provided at grade, the carriageway **must** be narrowed to 5.5m max, or two one-way lanes of 3.2m wide max provided with a central refuge between.
- 4.107 Spacing should be at least 100m offset.
- 4.108 At key nodal points, social exchange space and informal seating **must** be provided.



Zebra/ parallel crossing.



Cycle priority crossing.





- Pedestrian / cycle priority crossing Shared space/ informal crossings Urban realm - Buffer/ street furniture zone _____ Ramp to raised table / crossing \rightarrow Vehicle movement Cycle movement Cycle route transition zone

Junction 3

Latton Avenue / neighbourhood street

The junction where a neighbourhood street joins or crosses the Latton Avenue could either form a three-arm T-junction or four-arm crossroads.

- 4.109 Copenhagen style junctions **should** be used for crossing neighbourhood street(s) to give pedestrians on Latton Avenue higher priority than vehicles turning into / out of neighbourhood streets. Informal crossings **could** be acceptable in situations where traffic flows are lower.
- 4.110 The Copenhagen junction **must** be provided on a raised table to manage traffic speed and give active travel users priority over vehicles.
- 4.111 For cyclists, where there is a bi-directional cycle route on the side street side of Latton Avenue, the cycle priority crossing **must** allow continuous flow for cyclists.
- 4.112 Sufficient set back / variation in the alignment of the cycleway (if required) **should** be provided to allow a vehicle to wait between the Latton Avenue carriageway and cycle lane – allowing continuous vehicle movement.
- 4.113 Further informal crossings over Latton Avenue **should** be provided in situations where there may be a desire to cross Latton Avenue or where the junction is on a primary or quiet active travel route.
- 4.114 Spacing **should** be at least 60-80m between neighbourhood streets/ side roads.
- 4.115 On a primary active travel route both footways on the neighbourhood street **must** be continuous to Latton Avenue.



Junction 4

Latton Avenue / Play street on quiet active travel route

Active travel routes require crossing design to promote continuous flow of cycling and walking.

- 4.116 For pedestrians, an informal crossing should be provided over Latton Avenue at carriageway level with surface dressing to denote the crossing. Where there is higher crossing demand in more central areas or near schools, formal crossings such as zebra crossings for pedestrians and parallel crossings for cycles **must** be provided.
- 4.117 Formal crossings **should** be provided on a raised table at footway level to encourage lower traffic speeds and give pedestrians and cyclists a more continuous flow.
- 4.118 On raised tables the Latton Avenue carriageway width **must** be narrowed to max 5.5m to reduce crossing distances and revert to the standard carriageway width immediately adjacent to the crossing.
- 4.119 Where an informal crossing point is provided at grade, the carriageway must be narrowed to 5.5m max, or two one-way lanes of 3.2m wide max provided with a central refuge between.
- 4.120 Spacing should be at least 100m offset.



Fishgate, Preston.



- Pedestrian space/ cycle priority crossing
- Cycle space/ informal crossing
- Urban realm Buffer/ street furniture zone (can incorporate soft landscape)
- Car parking
- Carriageway
- Soft landscape/ SuDS
- Pedestrian / cycle priority crossing
- Shared space/ informal crossings
- Ramp to raised table / crossing
- Vehicle movement
- Cycle movement
- Cycle route transition zone

Junction 5

S2 Local Street / active travel route

As with Junction 4, this junction should promote continuous flow for pedestrians and cyclists.

- 4.121 For pedestrians, a formal crossing in accordance with LTN 1/20 must be provided over the secondary street to allow pedestrian movement from any of the four arms.
- 4.122 For cyclists, a formal crossing must be provided giving continuity over the secondary street as shown.
- 4.123 The crossings must be provided on a raised table at footway level to encourage lower traffic speeds and give pedestrians and cyclists a more continuous flow.
- 4.124 Spacing should be at least 100m offset.



Junction 6

S3 Neighbourhood Street / S6 car-free street

This junction between a low-traffic street and carfree street has less potential for conflict between users and can be used to emphasise high-quality and continuous walking and cycling routes.

4.125 Shared surface zones should be coordinated with active travel crossing points to provide an crossing in accordance with LTN 2/95 that spans the length of the car-free street and gives visual continuity to the car-free street.

4.126 Spacing should be at least 40m offset.



French example of informal table crossing.



- Pedestrian / cycle priority crossing Shared space/ informal crossings Ramp to raised table / crossing \rightarrow Vehicle movement Cycle movement Cycle route transition zone

The key components of open space across the masterplan are the community plaza, neighbourhood nodes including gateway spaces and those open spaces described in 'Section 02: Nature'. Essential principles and requirements are described here but the design of these spaces should be developed in collaboration with residents, stakeholders and different user groups to promote vibrancy, safety and inclusivity.



Integrated planter and street tree.



High quality public realm materials, Leonard Circus, Hackney.



Well designed public realm surface treatments enhance pedestrian and cycle priority, Copenhagen



'In the round' market building, Copenhagen.

Neighbourhood node requirements

- 4.127 Larger neighbourhood nodes **must** be 4.131 The square **must** include a multi-purpose, provided as focal points for every area of flexible market building with frontage on all residential development of approx. 200 homes. sides. The design should be innovative and Indicative locations are shown on the public distinctive in line with its role as a marker at space network diagram at the beginning of the heart of the new community. this section. These should be supplemented 4.132 The material treatment of the community by other greens and pocket parks or nodes plaza area **must** be high-quality and distinct of varying scales at natural focal points or from adjacent landscape treatments. intersections.
- 4.128 Neighbourhood nodes should aid wayfinding and the space and infrastructure provision should be appropriate to the scale of the node. At the smallest scale this could be shaded seating and a play element.
- 4.129 Larger nodes **should** provide a wider range of infrastructure, including:
 - Public seating
 - Tree(s) to provide shade
 - A drinking water point
 - Cycle parking
 - Space for informal play
 - · Integrated or incidental playful elements
 - Waste & recycling bins
 - Safe lighting levels
 - Art
- 4.130 Node spaces **should not** require fenced enclosures or railings and should be well integrated with the street network.

Community plaza

- 4.133 The plaza **must** be well enclosed with terraced/ connected buildings an all sides except facing the park, which **must** be open.
- 4.134 The school **must** have strong frontage to the square and to the park at the north corner,
- 4.135 Buildings fronting the square **should not** have railings/ fencing facing the square.
- 4.136 Items that **must** be included at the plaza:
 - Electrical points for events/ market trading
 - Area for informal play and community events unobstructed by fixed street furniture.
 - Trees and SuDS/ rain gardens.
 - Public seating
 - Waste & recycling bin
 - Water fountain and water connection point
 - Integrated public art that has been designed with the community as part of a wider art strategy.
 - Playable objects
 - Safe lighting with adjustable lux levels.

04/ Public space **Public open space design**



Play strategy

Play and recreation will be a key driver of a healthy and uplifting environment, helping to form the identity of Latton Priory and to support different character areas with well-considered and wellintegrated design.

A range of safe and accessible play and recreation opportunities will cater for different ages, groups and abilities.

It will be socially, mentally and physically engaging and will comprise a hierarchy of play and recreation infrastructure including:

Doorstep play

local areas for play (LAP) spaces very close to homes, children will have independent access to safe play spaces from a young age. Play will also help to create a vibrant and social public realm.

Street play / play-on the way

Through incidental play along key active travel routes such as the greenway, as well as along car-free play streets where these are on active travel routes, play and activity will be embedded into everyday life and will encourage activity and playfulness for all ages.

Local play

Neighbourhood play will be available within a short walk from all homes. It will comprise locally equipped areas for play (LEAPs), neighbourhood parks and green nodes.

Destination Play

Play located further from homes will include neighbourhood equipped areas for play (NEAPs) as well as trim/play trails, allotments, multi-use games areas (MUGAs), sports pitches and playing fields. School grounds will also provide multi-functional and multi-purpose play opportunities.



Through the provision of car-free play streets and Use of topography, water and characterful built form at Max Roach Park, Brixton by Muff Art and Architecture.



Bespoke play equipment and ground markings that can be used in different ways at Superkillen Park, Copenhagen by BIG

See also: Movement - Site-wide vehicular movement Public Spaces - Multi-functional Streets EFDC Local Plan Policy DM5 and DM9 EFDC Green Infrastructure Strategy HGGT Vision and Design Guide Active Design Guidance, Sport England Design for Play - Design Principles, Play England Safer Parks: Improving access for women and girls



Play for different ages and groups that is flexible and aids vibrancy at Westfield, Stratford

Play strategy requirements

- 4.137 A site-wide play, recreation and sport strategy **must** form part of the site-wide public realm strategy or design code that is in line with the play strategy diagram opposite.
- 4.138 The play strategy should be integrated with blue and green infrastructure, art and wayfinding, active travel and architecture. Play areas close to heritage assets should explore the interwining of play and heritage
- 4.139 Doorstep play, street play and local play must be well integrated, close to homes and community buildings and should not be closed off with fences or railings. It should allow safe access, natural surveillance and overlooking.
- 4.140 Connectivity with the wider community must be promoted through new or improved links to existing play spaces in surrounding areas and new play infrastructure along key routes.
- 4.141 The design of play equipment and the area around it **must** be positive, purposeful, bespoke and characterful. Design should draw on the site or more unexpected creative elements.
- 4.142 Provision must be diverse, ranging in scale, formality and user groups including differing abilities, neuro-diversity and the needs of women and girls and older children/ teenagers.
- 4.143 Play provision should provide a wide-range of experiences, including non-prescriptive elements that allow for interpretation, creative risk-taking and challenge. The area surrounding play spaces should be designed with opportunities for unstructured play, including low hedges or streams.
- 4.144 Seating, bins and lighting must be provided near to play spaces. Destination play and recreation **must** include access to public toilets.
- 4.145 Play equipment should be sustainable, durable and easy to maintain, prioritising natural materials.

04/ Public space Play and recreation



Strategic Design Code / Latton Priory / JULY 2024

Key strategies for a compact, human-scale built form

- Use the setting and topography of the site to inform the built form, including the distinctive roof forms found locally.
- Allow Latton Priory to sit comfortably in its setting through scale, form, sensitive boundary treatments. Consider key views between Harlow and natural site and heritage assets.
- Create the character of a community nestled on the hillside with an appropriate scale in relation to Harlow.
- Maximise the potential benefits of passive solar design through effective site layout.

An appropriate density and built form is required for vibrant, sustainable places and viable services. The sloping site means that building heights will be limited in order to preserve strategic views. A compact block form will therefore be required to deliver this density whilst responding sensitively to site conditions.

Compact development will maximise the land available for high-quality landscape and biodiversity and will support walkable, legible and human-scale streets, and overlooking of open spaces.

On most parts of the site, the best way to achieve this will be small perimeter blocks with back-toback distances that are shorter than in conventional suburban developments. Reduction in rear garden amenity will be balanced with generous, high-quality public space that supports people and nature.

•	See also:
•	Nature - Greenway and green fingers
	Public Space – Public space typologies
•	Movement – Active travel network
•	Resources – Passive design
•	EFDC Local Plan Policy SP2, SP3 and DM9
•	HGGT Vision and Design Guide
•	Essex Design Guide: Walkable Neighbourhoods



Site-wide density strategy



Highest density in local centre, key nodes and STC. High density along key connections around local centre Mid density around key connections and neighbourhood nodes Low density at edges away from key routes / spaces Lowest density at interface with ancient woodland

Block structure and density requirements

- 5.1 The overall layout must utilise compact perimeter blocks that support active travel and respond to site constraints and strategic green infrastructure.
- 5.2 Block structure **should** be in line with the block structure shown in the site-wide strategic diagrams in this code, with flexibility in precise dimension and geometry. Blocks must not be combined to create larger blocks. Smaller blocks **could** be tested.
- 5.3 Block structure **must** respond to key strategic views and vistas and maximise opportunities for further views to site features and landmarks.
- 5.4 Block structure must be designed to work with the existing topography as far as possible so that earthworks are minimised and built form reflects the topography of the site.
- 5.5 The site layout must be planned to address steep gradients without the need for excessive retaining walls. Where it is shown that retaining walls cannot be addressed through alternative layouts, these **should** be no higher than 0.8m.
- 5.6 Block size must be designed to encourage walking and cycling. Block dimensions should be as shown in the diagram opposite. Where density is higher, or site dimensions are particularly constrained, block sizes should be at the smaller end; where density is lower, blocks could be at the larger end of the scale to reflect the more dispersed character.
- 5.7 Blocks must be orientated to maximise north-south frontages to dual-aspect homes. Proposals should aim for at least 75% of dualaspect homes to have predominantly northsouth facing aspects.
- 5.8 Block size and typologies must vary across the site in line with the density strategy shown left, as well as the character of the street or space that the building fronts on to.



Long side of perimeter block: Maximum 75m frontage to frontage. Orient with the shape and direction of contour lines where possible. Orientated to face predominantly north/ south where possible.

Perimeter block dimension ranges and factors affecting orientation. Geometry is indicative only. and not an illustration of proposals.

Short side of perimeter block: Minimum 32m*, maximum 48m *where smaller dimensions are proposed innovative typologies must be shown to provide adequate amenity and privacy

It is important that frontages vary to reflect different characters and hierarchies and to ensure variety and interest across the masterplan. The placements of doors, windows, balconies and terraces as well as roof forms and the size and design of the space in front of the building will contribute. So will the relationship between neighbouring buildings and the density and continuity of the building line.

Characteristics of building typologies are described on these pages. The following page describes specific frontage requirements for key locations, accompanied by an illustrative strategy diagram showing how the requirements could be met.

Terraced houses

Typologies with low form factor (ratio of external wall to floor area), such as terraced houses and maisonettes, lose less heat and are more energy efficient than other house types. They also provide a well-defined street edge, activity and natural surveillance, making streets and spaces feel safer and more vibrant. Types of terraces include:

Standard terrace

- Provides the most robust edge and maximum natural surveillance.
- Suitable where site constraints limit block size as the plot size is small relative to dwelling size.
- Character can vary greatly depending on frontage width, articulation, roof form and entrance/ threshold design.

Broken terrace

- Broken parapet line or set-backs at upper floor(s)
- Frontage has strong rhythm and interest.
- Varies the sense of enclosure to a street or space whilst maintaining good overlooking.
- On-plot parking behind the building line keeps the windows of the home close to the public realm and could be converted in the future.
- First-floor terraces can provide more overlooking and activity plus extra amenity where required.

Mews terrace

- Frontage widths, heights, roof forms and private thresholds will be of a smaller scale and pared-back character compared to standard terraces.
- Likely that the parapet line will be continuous so that the terrace reads as a single entity, with individual homes marked by entrances and thresholds.
- Depending on the width required to create an intimate street (approx 8m frontage to frontage), the internal layout may need to be planned carefully to consider privacy, e.g staggering habitable rooms.

Detached or semi-detached houses

Density and character can vary greatly depending on frontage proportions, separation distances and ratio of plot sizes to building footprint. In order to maintain appropriate density, vibrancy and efficiency of land use, detached and semi-detached houses should generally be used in their most compact form.

Semi-detached and compact detached homes

- Do not offer as much natural surveillance, activity or form factor benefits as terraced houses.
- Can be useful to provide overlooking on secondary / narrow aspects of blocks where a row of terraces would be impractical.
- Can be useful for accommodating bin and cycle access and storage between dwellings where threshold depths are too small to accommodate these at the front and there is no other access to the rear.

Dispersed detached house typologies

- Contributes least to a vibrant, safe public realm and least land and energy efficient.
- Use of this typology must be limited to specific areas and justified in placemaking terms e.g. to create a rural character next to the ancient woodland.



Strong terraced rhythm through repeated roof forms at St Chads, Tilbury, by Bell Phillips Architects.



Smaller scale terrace appropriate for mews streets, Marmalade Lane, Cambridge, by Mole Architects.



Compact semi-detached houses to maximise overlooking at St Chads, Tilbury by Bell Phillips Architects.



Broken terrace with terraces overlooking a shared garden. Brick House, Birmingham, by Howells



Broken terrace with integrated parking, Knights Park, Eddington, by Alison Brooks Architects.



Compact detached house for corner interest and secondary frontages at Great Kneighton, by Proctor and Matthews Architects.

Larger building typologies

Larger buildings such as apartments and mixed use blocks should be used to help define key open spaces and provide density and focal points in the local centre and at key corners. Integration into the street scene and a coherent relationship with adjacent houses can be achieved through sensitive use of scale, materials, modulated facades, roof forms and rhythm.

Some typologies, such as schools or specialist housing will require larger buildings and the location of these will need to be carefully considered to contribute to the public realm and maximise opportunities for visual and physical connections between dwellings / communal spaces and the surroundings.



Apartment typology to address a key corner, Marmalade Lane, Cambridge. Mole Architects.



Apartment block form integrated with housing ,The Avenue, Saffron Walden, by Pollard Thomas Edwards.



Corner buildings should maintain the building or step forward intentionally and fit the angle of the street.

Corner houses

Whilst all buildings need to positively address all aspects they face, key corners require specific corner house or apartment typologies to minimise blank rear garden frontage whilst providing adequate amenity. 'Corner houses' will be specifically planned to strongly address both aspects, with windows to habitable rooms on both. This could take the form of an L-shaped plan or innovative typologies such as inter-generational living with 'granny annexes' to the rear, as illustrated here.

Corner built form requirements

- 5.9 All blocks **must** have built form on the corners and all corner building frontages **must** contribute to a high-quality public realm on both aspects, addressing the highest ranking street, open space or view most strongly
- 5.10 Built form on corners **must** be designed to fit the angle or curve of the street and **must** maintain the building line or step forward intentionally to provide focal points or pinch points/ book ends.
- 5.11 At intersections between key routes, apartments or specific 'corner house' typologies **must** be used in accordance with the table across and description on the previous page. 'Corner house' typologies **must** also be used where a secondary frontage of a block is not well overlooked.
- 5.12 The design of 'corner houses' **must** be considered as part of a set of corner typologies at each junction that relate positively to each other. At primary intersections, all four corners **should** be 'corner houses' or apartments. At intersections of tertiary and local routes, there **should** be two 'corner houses' opposite each other- see diagram across.

Active, high-quality frontage requirements

- 5.13 Typologies **must** be provided in accordance with the frontage requirements table.
- 5.14 Blank frontages **must** be minimised. Bin and bike stores for larger buildings **should** be integrated.
- 5.15 Boundary treatments visible from the public realm **must** be designed as part of a highquality streetscene e.g. brick wall or hedges.
- 5.16 All ground-floor dwellings **must** have principal entrances to the street, which are clearly defined through the architecture. Doors with direct street access **should** have some defensible space for separation from public space.
- 5.17 Where there is an absence of, or minimal defensible space between public and private space, anti-graffiti measures **must** be included, e.g. through window placement, material selection or non- destructive climbing plants.
- 5.18 Non-residential buildings, including the schools, **must** be sensitively designed to ensure integration with surrounding buildings. They should act as positive, civic landmarks, whilst avoiding being institutional in character.
- 5.19 Roof forms **must** vary to support character and wayfinding, with more variation around key nodes and primary junctions and more consistent roof lines on smaller streets.
- 5.20 Roof forms **should** reference distinctive arrangements in the context, particularly where roof forms respond well to sloped topography.
- 5.21 Where east-west orientated blocks are used along the ridgeline, the impact on long views **should** be mitigated through roof form articulation.
- 5.22 Extensive flat roofs on larger buildings **should** be avoided in order to prevent a dominant and bulky silhouette.

Location/ street type	Permitted typologies	Other frontage
Neighbourhood nodes	Apartments including mixed use	• High density of
High street	• Standard terraces	• Small set-backs:
Latton Avenue Local streets	• Broken terraces	 Low planting. N required.
Greenway	• Generally, mixture of standard terraces and broken terraces	• Medium - high c
Wetland park frontages	 Broken terraces where parking strategy states on-plot parking behind building line. 	Small set-backs:Low planting. N
	• Apartments inc. mixed use permitted in local centre/ key nodes.	required.
	 Compact detached or semi-detached houses permitted at eastern edge next to ancient woodland. 	• Maximise overlo to wetland par
Green nodes with play	Apartments including mixed use	• High density of
space	• Standard terraces	• Small set-backs:
Park frontages	• Broken terraces	• Low planting. N required.
Green fingers	Standard terraces	• Medium - high c
	• Broken terraces	• Undulating roof
		• Strong rhythm r
Car-free play streets	Mews terraces	• High density of
	• Broken terraces	Low-scale conti
		 Low planting or required.
Other streets forming	Standard terraces	• Medium - high o
'quiet active travel routes'	Broken terraces	• Varied set-backs
	 Apartments inc. mixed use permitted in local centre 	• Low planting or required.
Green edges	Broken terrace	Medium density
	 Compact detached houses 	• Varied set-backs
	 Semi-detached houses 	 Low planting or required.
Ancient woodland	• Detached	• Low density of
frontage	Compact detached	• Low planting to
	• Semi-detached	• Varied and disperies character.

Frontage requirement table

e requirements

f building line - 80-100% built form s: 0.5m - 1.5m, smaller in local centre No walls or fences except for bin/ bike stores if

density of building line - 70-90% built form s: 0.5m - 2m, smaller in local centre No walls or fences except for bin/ bike stores if

looking while complementing/ providing backdrop arks/ greenway. Consider roof terraces. If building line - 80-100% built form s: 0.5m - 1.5m No walls or fences except for bin/ bike stores if

density of building line - 70-90% built form ofline could reflect green setting. a reflect movement function of green finger. of building line: 80 - 100% built form. tinuous frontage or low walls except higher for bin/ bike stores if

density of building line - 70-90% built form ks: 0.5m - 2m or low walls except higher for bin/ bike stores if

ty of building line 60 - 80% built form. ks: 0.5m - 2m or low walls except higher for bin/ bike stores if

f building line: 50 - 70% built form. o suit woodland edge character. No walls/ fences. persed frontage to complement woodland

or sustainability, vibrancy and land efficiency and and density strategy
Illustrative site-wide typology strategy

*

_ _

 \bigcirc

 \bigcirc

Note that this highlights specific corner typology locations and how other typologies could be distributed in line with the frontage requirements described opposite.



Heights strategy

The overall heights strategy is based on the Strategic Masterplan Framework heights strategy with refinements to suit relationships with context and placemaking.

Local landmarks

While general building height ranges span large areas depending on proximity to the ridgeline or other site and placemaking factors, it will be important to include variety in building heights and roof forms within these areas to avoid monotonous streetscapes and skylines. The requirements opposite indicate where moments of height should be used as landmarks at key nodes or along vistas. These height markers will avoid the development appearing as a solid mass of built form, by expressing key moments or landmarks in long distance views of Latton Priory, as is typical for hillside settlements.

Street enclosure

Whilst all streets will need to have a residential scale, the ratio of building height to street width will have a significant impact on the character of the street. Taller buildings and narrower street widths give a greater sense of enclosure. Given limited building heights at Latton Priory, and minimum street widths as defined in the street design section, there will need to be careful consideration of how to give enough of a sense of enclosure for vibrancy, activity and character.



Taller building element at key corner at Charlton, Greenwich by Peter Barber Architects.



Extra floor to provide height landmark at Abode, Newhall, Harlow by Proctor and Matthews Architects.

Building height requirements

- 5.23 The overall heights strategy **should** be generally in line with the diagram opposite. Where there are deviations, these **must** be justified in technical or placemaking terms.
- 5.24 Building heights **must** be tested for visual impact on key points in the surrounding areas alongside proposed ground levels that minimise the need to alter existing topography. Built form adjacent to existing dwellings must be tested for impact on those residences and amenity.
- 5.25 Local landmarks of taller buildings or building elements **should** be provided at the points noted below and the articulation of these should be tested through street view perspectives and longer perspectives from Harlow. Where possible these **should** be coordinated with key frontages and groupings. See section 06: Identity. For example:
 - Around neighbourhood nodes and green nodes.
 - At key site gateways and local centre gateways.
 - At intersections between north-south fingers, and the greenway or Latton Avenue.
 - At intersections between the greenway and Latton Avenue and at regular points along greenway and Latton Avenue.
 - Either side of key vistas, including north-south green fingers and strategic views.
- 5.26 Sense of enclosure of streets **must** vary according to street type. Where this cannot be achieved due to limitations on building heights, a sense of enclosure **should** be incorporated by other means such as tree planting or house typologies with terraces for an increased sense of overlooking.
- 5.27 Floor-to-ceiling heights at ground level **should** be at least 2.5m throughout and higher where required for non-residential uses.

Illustrative site-wide building heights strategy



Key strategies for a distinctive identity

- Draw on the best of key features and characteristics of Harlow New Town and Epping, as well as responses to the landscape context of development clusters within the new neighbourhood.
- Incorporate variety, vibrancy and wayfinding into streets and open spaces, punctuated by moments of joy expressed through architecture, art, and landscape design treatments.

This section describes the strategic approach to key building frontages across the site. These frontages should be identified in any proposals and their design should contribute to a positive character that draws on successful aspects of the context. Local references should be interpreted in imaginative ways to create a contemporary, highquality response and avoid pastiche or generic architecture.

Key frontages

The diagram opposite highlights where key frontages should be located in relation to the open space and movement network. The aim of giving particular emphasis to these frontages is to:

- identify key routes/ spaces and reinforce hierarchy.
- provide quality, character and interest to key public spaces.
- add uplifting moments and variety.
- provide coherent built form around key spaces.
- provide well-defined framing and enclosure to key spaces and maximise natural surveillance and overlooking to encourage its use and vibrancy.
- aid wayfinding by providing memorable landmarks that can be identified from along key vistas.
- guide movement along key routes.

Identity and sense of place must be reinforced through clear wayfinding and legibility, drawing on the best of the context to ensure that the new place is memorable and locally distinctive. Detailed design codes will demonstrate how building identity, including elevations and materials, responds to character areas, landscape and public realm context.

See also: Context Nature Public Spaces – Public space typologies Built Form – Frontages EFDC Local Plan Policy SP2, SP3 and DM9 HGGT Vision and Design Guide Harlow Design Guide SPD Harlow Town Centre Framework SPD Harlow and Epping Conservation Area character appraisals







Grouping of buildings around a junction at Knights Park, Eddington. Cambridge by Pollard Thomas Edwards.



Example of landmark frontage to key open space, Southwold, by Ash Sakula Architects.

Distinctive frontage requirements

- 6.1 The primary movement network **must** be articulated with special emphasis on frontages and buildings relating to gateways, vistas and key routes in line with the strategy diagram, shown opposite.
- 6.2 A secondary wayfinding strategy **must** be established with marker buildings at key points along quiet active travel routes, as shown. There **should** be a consistent approach to building features to identify these markers.
- 6.3 Neighbourhood nodes and key community spaces **must** be framed by a group of buildings that have a legible and distinctive identity. Grouped buildings do not have to be the same style but **should** have connecting or common features to provide coherence.
- 6.4 Connecting features do not have to be used in the same way on all the buildings in the group, but **must** clearly relate to each other. Simplified connecting features **could** be used on buildings outside the groupings to express rhythm and continuity.
- 6.5 Connecting or common features **must** be integral to the design of the building. Connected or common features **could** include: upper floor projections; coherent roof forms that work as a set; distinctive geometric compositions of built form; projecting corner windows; characterful combinations of materials.
- 6.6 Key open spaces or views **must** be framed by special frontages that contribute to the quality and character of the space as well as the perception of overlooking and activity.
- 6.7 Successful and distinctive precedents in the context **should** be used to inform the composition of groupings and the design of key buildings and frontages. Examples of relevant references are provided on the following pages.

06/ Identity Wayfinding and sense of place

Illustrative site-wide groupings and wayfinding strategy



Wayfinding and groupings

- --- Sustainable transport corridor
- $- \rightarrow$ Key site connection route
- $\cdots \rightarrow \mathbf{Q}$ uiet active travel route, low car movement
- --->Key green connection
 - Neighbourhood node
 - 🖌 Gateway
 - Primary gateway, vista and route markers
 - Quiet route markers
 - Groupings around nodes inc. community plaza
 - Landmark frontage to key open space or view

Harlow context

From Gibberd's masterplan through to contemporary developments, Harlow has a rich heritage of progressive architecture and urban planning that should help inform the identity of the new community at Latton Priory. The distinctive aspects of the new town are described in the following documents, which should be referred to for character appraisals to inform future development:

- Harlow Design Guide SPD
- Harlow Town Centre Masterplan Framework SPD
- Harlow and Gilston Garden Town Design Guide

Particular aspects of the prevailing New Town character that could inform identity, include building arrangements around hatches and other open spaces, consistent building lines and open fronts to houses.

There is also scope for drawing on the character of Harlow's historic conservation areas, particularly historic groupings along high-streets and around open spaces.

Modernist and historic articulation, motifs, forms and palettes could also be interpreted in a contemporary way to inform a distinctive identity that strongly relates to the context.





























View into High Street (east) Source of images: Museum of Harlow Extract from Old Harlow Conservation Area character appraisal showing landmark building grouping around key gateway to the high street.



Extract from Harlow Town Centre Framework SPD showing features and materials specific to Innovative housing, Abode Newhall, Harlow by Proctor and Matthews Architects. Harlow Town Centre.



Views and landmark / corner buildings

Epping context

Epping high street provides references both in composition of buildings and more detailed aspects of built form. The origins of Epping as a medieval market town has resulted in a distinctive pattern of built form along the high street with variety and hierarchy that relates to building function and the public realm.

The three towers – the Civic Offices, St John's Church and the water tower – punctuate the townscape and provide focal points from open spaces and gateways to the high street. Hierarchy of built form is also seen in the historic civic or social buildings, such as the old inns, being 2.5-3 storeys with cart door entrances to the side. Historic residential and ancillary buildings are lower in scale with more modest facades and a strong horizontal emphasis.

The setting back of buildings at points along the high street adds to the varied character and creates a sequence of spaces for civic life such as the weekly market or seating.

The historic farmsteads that are common across the district could be referenced for character arising through composition and grouping of built form and the spaces created.

Shown here are some typical examples of farmstead groupings in the district as well as the farmstead at Latton Priory. Whilst they may vary between L-shaped or E-shaped, they are all configured around a central space. The position of buildings, as well as their geometric forms, contributes to the overall character and coherence of the groupings.



Variety and quality along Epping High Street, highlighting focal points and enhancing the visual experience.



Focal point frontages around Church Hill open space at the gateway to Epping High Street.





E-shaped farmstead configuration at Torrells Hall, Willingale, Ongar L-shaped configuration at Stonards Farm, Stonards Hill, Epping







Pastoral influences, The Avenue, Saffron Walden. by Pollard Thomas Edwards.

Environmental design requirements Key strategies for environmental design Implement opportunities for energy efficiency at every scale – from site layout through to building elevations - with a target of net-zero operational and embodied carbon. of the project team at all stages. Minimise embodied carbon and optimise passive design measures. Be resilient to rising fuel costs and the effects of climate change, including more extreme temperatures, increased rainfall and intense weather events. **Climate resilience Climate mitigation** Epping Forest District Council declared a climate Alongside minimising impact on the environment, emergency in 2019 and made a commitment to 'do buildings and open space will need to be designed everything within its power to become a carbon neutral so that the new neighbourhood can thrive in a district by 2030'. Sustainability standards at Latton changing climate, including hotter summers, colder

Priory must reflect this commitment. Aspects winters, increased rainfall, droughts, extreme of sustainable design are woven throughout this weather events and poorer air quality. design code, including extensive green and blue infrastructure, ecology and biodiversity, compact walkable neighbourhoods and passive design and orientation of built form.

through the efficient use of infrastructure in line with the principles of compact walkable neighbourhoods robust stewardship measures will help to ensure and working with the existing topography as far as these benefits are maintained in the longer term. possible to avoid unnecessary excavation. Energy in use will be minimised through the energy hierarchy and 'fabric first' approach, with renewable energy and passive design measures. This will be reflected in the orientation and form-factor of built form and dual-aspect, highly-insulated buildings.

Minimising hard surfaces/ highways and maximising climate resilient green and blue infrastructure will help to reduce the urban heat island effect and reduce susceptibility to flooding and extreme At a strategic level, resources will be minimised weather events. A move towards smaller private gardens and more significant public open space with

> The street hierarchy includes car-free streets that are narrower to provide a level of enclosure for shaded active travel routes. Alongside external shading and trees to south-facing frontages this can also help to maintain comfortable homes.



Distinctive passive design, Goldsmith Street, Norwich by Mikhail Riches.



Seating and tree planting for shade.

	7.0	
See also:	•	
Nature	•	
Movement – Active travel network	7.9	
Public spaces	•	
Built form – Passive design	• • •	
EFDC Local Plan Policy SP2, SP3 and DM9	•	
HGGT Sustainability Guidance and checklist		
Essex Design Guide: Walkable Neighbourhoods		
LETI Climate Emergency Design Guide	•	

- 7.1 Sustainability **must** be embedded at the earliest stage. A sustainability consultant **must** be part
- 7.2 Development proposals **must** be accompanied by the HGGT Sustainability Guidance checklist and supporting information. Proposals should meet the highest level of sustainability on the checklist to target net-zero carbon and waste by 2030. Deviations must have technical justification or evidence of an alternative approach meeting the aims of the development.
- 7.3 Proposals **must** be shown to work with existing topography as far as possible.
- 7.4 Passive design measures **must** be a key driver in the site layout and built form design.
- 7.5 Proposals must allow for best-practice insulation standards and associated wall thicknesses in line with Passivhaus principles.
- 7.6 Plans **must** identify how renewable energy infrastructure e.g heat pumps or batteries will be sensitively integrated into the layout and buildings.
- 7.7 The energy strategy **must not** include fossil fuel use. On-site renewable energy sources **must** be prioritised and opportunities for utilising waste heat across different uses should be explored.
- 7.8 Energy efficiency in building construction, for example through innovative and modern methods of construction, must be explored at an early stage.
 - Roof forms of all buildings must be designed to consider optimum solar orientation for photovoltaic panels (PVs) or bio solar green roofs. PVs on sloping roofs must be carefully designed, particularly due to longer views from Harlow, with PV panels mounted flush with the roof finish.

Key strategies for adaptability and future-proofing

- Accommodate future needs and lifestyles. New buildings will be flexible and adaptable, including the capacity to incorporate future innovations in energy conservation and technology.
- Encourage a long-term, active community through a mix of housing typologies and tenures and adaptable, accessible homes.
- Allow for future developments in travel modes, including reduced parking, EV charging and shared modes such as pick up and drop off points.

Adaptable and future-proofed

the environment now and in the longer term, development must be planned to accommodate changes in lifestyle, technology, the climate and social and economic changes.

Where possible, the adaptability of spaces should be considered to serve different uses at different times. For example, open space that provides parking during weekdays could be used as a market square at weekends. Similarly, community hubs may be used for flexible workspace during the day and cultural events in the evenings.

Multi-functionality will also support social 7.12 Buildings should be designed to adapt to sustainability and vibrancy through encouraging different user groups to share space and resources. The opportunities are particularly strong around school and Extra-Care facilities and space being shared with other social and community groups.

Key adaptability requirements:

- In order to meet the needs of people and 7.10 Proposals must consider future car parking trends i.e. reduced overall demand and increased shared car usage. Most car parking must be shared on-street or in car barns rather than within private curtilages. Potential future uses for those spaces **should** be illustrated.
 - 7.11 Homes **should** be designed to adapt to changes in accessibility requirements, family structures and lifestyle changes, such as increased home working. A range of innovative and adaptable housing **should** allow people to stay in the community through their life.
 - changing uses, particularly in the local centre and around key nodes. This will include higher ground floor ceiling heights and internal layout flexibility.
 - 7.13 Buildings and the public realm should be adaptable to accommodate new technology including transport, sustainability and waste / recycling services. This should not have a negative impact on the public realm.
 - 7.14 Social and community buildings and spaces should maximise opportunities for shared and multi-functional use.



Flexible community hub, Hammersmith and Fulham by RCKA.



APPENDICES:

Appendix A:

Latton Priory Strategic Masterplan Framework, June 2023 by Broadway Malyan Extract: Mandatory Spatial Principles.

Appendix B: Glossary of terms

Appendix C: Image References





Mandatory Spatial Principles









LATTON PRIORY

LATTON PRIORY

HARLOW & GILSTON GARDEN TOWN

MANDATORY SPATIAL **PRINCIPLES**

Introduction

This section presents the spatial elements of the masterplan framework which are shown by **Mandatory Spatial Principles.**

The Mandatory Spatial Principles on the following pages set out key principles covering:

- Land Use and Spatial Organisation
- Landscape Character
- Green/Blue Infrastructure and Strategic Views
- Access and Movement

These principles will need to be incorporated, or any alternative approach explained, in any future proposals for the neighbourhood

These mandatory principles establish the spatial concept and disposition of uses.

Future planning applications will be accompanied by detailed assessment and technical work to set the parameters of the proposed development in line with these principles.

MANDATORY SPATIAL PRINCIPLES LAND USE AND SPATIAL ORGANISATION

Mandatory Spatial Principles: Land Use and Spatial Organisation

- 1. Location and Arrangement of the Local Centre - will be positioned in the heart of the neighbourhood with primary access from the East-West Green Corridor and Latton Avenue and with frontage onto Latton Park to the east. The local centre will provide a mix of residential and non-residential uses including retail, community uses and employment. Nonresidential uses (retail, food / drink, adjacent education and community uses, which help animate the public realm) will be located at ground floor around the Plaza and Latton Avenue.
- 2. Location and Arrangement of the Plaza will be positioned on the eastern edge of the local centre, predominantly to the south of Latton Avenue and facing onto Latton Park. The Plaza will be designed to a suitable size to support the quantum of non-residential uses intended with retail, food/drink, adjacent education and community uses activating and fronting onto this space. The mobility hub will be within the Plaza.
- 3. Nodes nodes to provide public space should be located at central locations to residential areas for equal access from homes within the development. A minimum of two nodes to coincide with mini-mobility hubs (see Mandatory Principles for Access and Movement) should be provided to the east and west of the local centre. Further nodes and gateways will be provided with number/ locations fixed through design coding work.

- 4. Location of Latton Priory Primary School -The site for the primary school will be circa 2.1ha. The primary school will be a central component of the neighbourhood and will have frontage onto the proposed East-West Green Corridor to promote sustainable travel. It will have a car-free frontage / dwell space for parents. The primary school will be adjacent to the secondary school to facilitate a throughschool if required.
- 5. Location of Latton Priory Secondary School -The site for the secondary school will be circa 10ha. The secondary school will be a central component of the neighbourhood and have frontage onto the East-West Green Corridor to facilitate sustainable travel. The frontage will face onto the Plaza, activating it and using it as dwell space. It will have frontage onto and be visible from Latton Park. It will be adjacent to the primary school to facilitate an all-through school if required. School pitches will be located within the no-build zone south of the school and will be designed in accordance with Sport England standards.
- 6. Location of Gypsy and Traveller Site will be positioned to allow for good access to the road network. The site will allow for 5 pitches in line with policy, with the final configuration to be determined upon consultation. It will not be positioned near the existing gypsy and traveller site in Fern Hill Lane. Three potential sites are shown opposite but only one site will be provided.
- Build-to Line This follows the ridgeline in the site. Land to the south will be retained for public open space, landscape or other appropriate open uses including recreational uses and the school playing pitches.

- Formal Open Space Community cricket pitch and/or football pitches will be located south of the 'build to' line as part of the new Rye Hill Park and will be designed in accordance with Sport England standards.
- Other Open Space (parks and gardens, amenity, natural/ semi-natural greenspace, play space, productive landscape, green fingers) - see Mandatory Principles for Landscape, Green/Blue Infrastructure and Strategic Views.
- 10. SANG (Suitable Alternative Natural Greenspace) - see Mandatory Principles for Landscape, Green/Blue Infrastructure and Strategic Views.
- 11. **East-West Green Corridor** see Mandatory Principles for Landscape, Green/Blue Infrastructure and Strategic Views and Mandatory Principles for Access and Movement.

83

LATTON PRIORY



MANDATORY SPATIAL PRINCIPLES LANDSCAPE CHARACTER

Mandatory Spatial Principles: Landscape Character Areas and Landscape Interfaces

1. Landscape Character Areas

- **1a** The Southern Plateau will remain open in character and retained as a rural buffer and key open space feature of the site. The southern plateau is primarily south of the build-to line. It will be managed to provide for both biodiversity as well as recreation and productive landscape. The southern plateau incorporates Rye Hill Park (recreation, community sport pitches, productive landscape, heritage), secondary school pitches, areas of meadow land (rewilding) and areas of SANG (recreation and enhanced biodiversity). New trees will be planted along the southern edge of the site to enhance the wooded skyline as seen from Harlow Town Centre.
- **1b** Wetland Landscape The wetland areas along the northern site boundary (Northern Waterways) will provide for sustainable urban drainage and attenuation ponds, biodiversity gain, habitat creation and recreation. Recreational routes through the wetland to be defined to allow access without disturbing wildlife.
- 1c Eastern Woodlands New planting added to this area to enhance important existing treelines and woodland areas. These will be located in the Latton Priory Woods built-form character area (eastern residential area relating to Mark Bushes). New trees will be planted along the southern edge of the site to enhance the wooded skyline as seen from Harlow Town Centre.
- 1d Central Green Wedge & Greenways Open space areas within to be relatively informal parkland in character, with trees interspersed with areas of meadow and amenity grassland in the main park area. The planting will be arranged to retain key view corridors towards Harlow Town Centre, including but not limited to views from the NEAP which will be located in Latton Park.

2. Landscape Interfaces

- 2a Rye Hill Road interface (Western boundary) -The landscape will incorporate the retained roadside hedgerow and trees. Properties will be orientated to face Rye Hill Road and set back to reflect the established character west of the road, with intervening tree planting to strengthen the wooded character of the street.
- 2b Wetlands interface (Northern boundary) -SuDS basins and connecting swales will be provided along with landscape interventions with native wetland trees, shrubs, grassland and marginal plants for amenity and ecological benefit. Site boundary hedgerow will be retained and enhanced with further tree planting. Recreational paths will provide connections between the development and areas to the north.
- 2c Ancient Woodland interface (Eastern boundary) - Buildings will be set back 25m from the woodland edge and be oriented to a landscape buffer comprising woodland planting, ecologically valuable grassland and a recreational footpath/bridleway.
- 2d Southern Plateau interface (west) The interface comprises open woodland planting on the highest ground with the framework of historic native field boundary hedgerows and meadow grassland reinstated beyond to the south, also incorporating allotments, orchard and play.
- 2e Woodlands interface Streets must have a strong woodland character, with buildings set back from the woodland edge while oriented towards it. Native trees and hedgerow planting will define the built edge. Meadow grassland and recreational routes will pass through the the woodland buffer and directly connect the neighbourhoods and SANG.
- 2f Parkland interface Parkland edge will include trees within areas of meadow or amenity grassland as well as an area of productive landscape.

LATTON PRIORY



Mandatory Spatial Principles

MANDATORY SPATIAL PRINCIPLES **GREEN/BLUE INFRASTRUCTURE AND STRATEGIC VIEWS**

Mandatory Spatial Principles: Landscape, Green/Blue Infrastructure and Strategic Views

- 1. **SANG** The natural and semi-natural open space which will provide suitable alternative natural greenspace (SANG) will be located in the southern plateau south of the extension of the green wedge / Latton Park. The SANG will allow for good pedestrian connections with residential areas, linkages with other open spaces, streets, provision of attractive walking routes with appropriately surfaced paths, open sight lines along walking routes, avoiding overhanging vegetation where this exists, access for dog walking with off-lead areas and facilities to attract dog walkers, secure boundaries where needed, biodiversity enhancements, seating, litter and dog waste bins, signage and interpretation, ongoing landscape management, play, tree groups, holding ponds, scrapes and swales, furniture and features, underground constraints or legal constraints. As SANG is intended to attract new residents arising from the relevant Masterplan areas the SANG provision should be located adjacent to the built parts of the site and designed to be visually and physically linked with it. (EFDC GI Strategy)
- 2. General Location of Pitches Sports Pitches are included in the secondary school and within Rye Hill Park on the southern plateau. Pitches will be designed in accordance with Sport England standards. A sensitive lighting strategy will be implemented. In response to the plateau location, flood lighting is not proposed.
- 3. Extension of the Harlow Green Wedge There will be a continuation of this existing landscape structure through the site. Its relation to the surrounding countryside and pedestrian rights of way is key to creating an integrated landscape.

- 4. Productive Landscapes Areas of productive landscape will be located to allow equitable access, at a maximum of 800m distance from all homes. Locations will include Rye Hill Park (allotments, and community orchard). Smaller areas of community orchards/gardens will be included: north of Dorrington Farm near to the western end of the E-W Green Corridor, at the intersection of the North-South green finger in Lower Rye Hill South and the East-West Green Corridor, within the primary school, in Latton Park and in the central open space within Latton Priory Woods built-form character area. Further smaller areas of productive landscape may be included in suitable locations for equal access and focal points.
- 5. Ancient Woodland will be protected and conserved with a 25m eco-tone buffer of grassland and native woodland along its boundary to provide a structured edge and enhance the wooded character. Housing will face this woodland to address the buffer for natural surveillance.
- 6. Green Corridors and Green Fingers There are two East-West Green Corridors proposed, a 'Super Greenway' and a southern branch, There are also five north-south green fingers proposed. These will provide a suitable green grid of connectivity for access, movement, outlook and ecology along with access to onwards connections. Green Corridors and Fingers must have suitable width for walking, cycling, planting and SuDS. Where possible properties will be orientated to overlook these spaces which will accommodate walking and cycling providing direct connections between the focal recreational and play spaces. Water management will be incorporated within the green corridors and especially in the green fingers where applicable , managing the transition of surface water from higher ground in the south, to the lower wetlands areas in the north. A natural and primarily native planting approach will be utilised.

- 7. Retention and Recreation of Field Boundary Structure - The existing site boundary hedgerows will be retained and historic field boundary hedgerows will be reinstated within Rye Hill Park and the SANG area. Where breaks in existing hedgerows are required for access and movement this should be justified.
- 8. Woodland Belts Existing belts will be retained and enhanced with new connecting native woodland planting in order to enhance the woodland character existing in these parts of the site and to create a wooded skyline when seen from Harlow Town Centre.
- 9. Play Spaces 'Play' will be at the forefront of the public realm and green infrastructure strategy, incorporating informal and formal sports and recreation, 'play-on-the-way' routes with playable landscape features, public art, outdoor gyms and natural playgrounds. One NEAP will be provided with additional LEAPs with equitable access also provided. Door-step play will be incorporated close to family dwellings and be well overlooked with safe and convenient access.
- 10. SuDS (throughout masterplan) will be sensitively and creatively integrated into the landscape, working with existing hydrology, topography and ecology and support character and place-making.
- 11. Habitat Creation and Management (throughout masterplan) - The development proposes to deliver a minimum 10% Biodiversity Net Gain with the promotion of biodiversity to be explored at every opportunity. This will be delivered through the provision of enhanced and newly created habitats, including the delivery of a landscape-scale coherent ecological network.

12. Strategic Views - to Dorrington Poplars and Riddings House grounds when seen from Harlow town centre will be incorporated into the masterplan. Existing woodland blocks will provide a backdrop to the proposed development along the horizon in views from Harlow town centre. New woodland planting will link these existing woodland blocks as it matures. Strategic views towards the Town Centre will be incorporated from Latton Park. There are views from the plateau south across gently undulating farmland towards the town of Epping and northwards towards Harlow (Harlow town centre being the prominent feature).

- A. Town Centre to Water Tower

- B. Town Centre to Poplars
- C. Between Water Lane and Poplars
- D. Between Town Centre and Green Wedge Extension
- E. Town Centre to Woodland Backdrop
- F. Between Southern Site Boundary & Epping Countryside
- G. Between Southern Site Boundary & Epping Countryside

8. Sensitive Lighting Design - development fringes, interfaces with natural habits (new and existing) and all ecological corridors will consider sensitive lighting design to preserve dark corridors, character and visual impact.

LATTON PRIORY



Mandatory Spatial Principles

MANDATORY SPATIAL PRINCIPLES ACCESS AND MOVEMENT

Mandatory Spatial Principles: Access and Movement

- East-West Green Corridor (Super Greenway)

 will be the primary east-west sustainable movement corridor across the neighbourhood. It will accommodate pedestrians and cyclists as well as any micro-mobility vehicles. The route will be established across the neighbourhood from the existing recreation ground to the north west to the local centre and on to Mark Bushes in the east. The corridor will facilitate sustainable travel across the site, particularly to the Local Centre and Plaza which will include the Mobility Hub.
- 2. North-South Green Fingers will be the primary north-south sustainable corridors across the neighbourhood. They will accommodate cycle and pedestrian movement and facilitate connections with surrounding existing routes north and south of the site.
- 3. Latton Avenue Latton Avenue will accommodate vehicles, pedestrians, cyclists and micro-mobility vehicles. It will be designed to discourage the use of private vehicles by making the route for such vehicles less direct than for sustainable modes. It will have a speed limit of 20mph and be designed accordingly. Priority will be given to active and sustainable modes at junctions. It will be designed to include green verges and street trees. Latton Avenue will pass through the local centre and the points shown on the adjacent plan.
- 4. **Plaza/Community Square and Mobility Hub** - will be located in the Local Centre in the area to the west of Latton Park. The Plaza will act as a dwell space for the secondary school and will also contain the Mobility Hub and more functional transport requirements on the north side. The Mobility Hub will act as an interchange between public transport and a range of sustainable transport options, as well as providing further related facilities.

- 5. Mini Mobility Hubs will support the main Mobility Hub in encouraging sustainable travel, facilitating the movement of residents living further away from the Local Centre via bicycles and other micro-mobility vehicles. One will be located on the west side of the neighbourhood within the green finger to the north of Latton Avenue. Another will be located on the east side of the neighbourhood within the green space.
- 6. **Potential Bus Stop Locations** All homes should be within circa 800m (or a 10 minute walk) of a Mobility Hub or the Sustainable Transport Corridor, and within circa 400m (or a 5 minute walk) of a local bus stop.
- 7. Key Active Travel Connection Points -Pedestrian and/or cycle routes within the neighbourhood will connect with these access points into/out of the neighbourhood to link with existing active travel routes in the surrounding areas.
- 8. Vehicular Access from Rye Hill Road There will be up to a maximum of two vehicular access junctions into the neighbourhood from Rye Hill Road. These will also provide cycle and pedestrian access.
- 9. Access from London Road Latton Avenue will connect with B1393/London Road at an appropriate stage and location to be determined. Priority will be given to sustainable modes of transport at this junction.
- 10. STC The primary function of the STC network is to provide direct sustainable travel connectivity between key destinations, primarily Harlow Town Centre. The series of strategic public travel routes will provide high quality public transport and active travel options that will connect existing and new communities and provide the standard for

exemplary sustainable travel as one element to achieve the mode share objective. The proposed STC is intended (where practicable) to be designed along its full length to give appropriate priority to active and sustainable modes over the private car (with associated journey time advantages in respect of public transport) to ensure frequent, fast and reliable services.

The STC is proposed to connect from the Local Centre to the north of the site through to Commonside Road and into Harlow Town Centre, with a terminus at the Mobility Hub in the Local Centre. The STC is proposed to accommodate dedicated facilities for walking and cycling and public transport, and will be designed to the STC Placeshaping Principles (where practicable).

- 11. SANG Route(s) A choice of shorter and longer recreational circular routes will be provided around the SANG to cater for dog walkers and also to support other walkers. These will vary from 2.3km-3km in length. Paths must be easily used and well maintained and if surfacing is to be provided in order to support greater accessibility this should be done in a sensitive way so as to avoid the site becoming too urban in feel within the SANG.
- 12. **Drover's Route** will be a recreational pedestrian, cycle and bridle route.
- 13. **Rye Hill Road Mitigation** Appropriate mitigation will be provided on Rye Hill Road as determined by the detailed transport assessment.
- 14. Concessionary Bridle/Cycle Route A concessionary bridle/cycle route to west of Mark Bushes connects to the reinstated drovers' route and existing bridleway at its southern end, further enhancing local cycle and bridle connections.



Active travel

Sustainable transport that involves activity, which is often free or low-cost and has associated health and wellbeing benefits. This includes walking, cycling and scooting.

Adaptability

The capability of a place, structure or system to adapt to changing conditions. These include social, economic and technological changes as well as climatic changes such as rising temperatures and more extreme weather events.

Adoption (of streets and spaces)

Where an authority, such as the local authority or highway authority adopts and maintains a public area that is essential to the functioning and appearance of development.

Biodiversity

The variety of plant and animal life in the world or in a particular habitat, a high level of which is usually considered to be important and desirable

Block structure

The shape of development between streets and spaces. Perimeter blocks are a common type of block structure that provide good frontage and overlooking/ activity to streets and spaces, as well as a clear distinction between public fronts and private backs.

Blue infrastructure

Infrastructure provision relating to water. This includes natural features such as rivers, streams and ponds and semi-natural features such as sustainable drainage systems and bio-swales.

Building line

A building line represents the alignment of the front face of the buildings in relation to a street or other public space. The nature of this line and its position in relation to the street contribute to the character and identity of a place. It may be straight or irregular, continuous or broken. A consistent approach to building line in an area type or street type helps to give it a coherent identity. (NMDC definition)

Build-to line

A line beyond which built development is not permissible except in special circumstances. This is to preserve key strategic views and the character of the ridgeline. The build-to line is stated in policy SP4.G.v of the EFDC Local Plan and shown in Map 2.3.

Bus Rapid Transit (BRT)

A fast and efficient priority bus service, located along the Sustainable Transport Corridors, making use of the latest transport technology. The Bus Rapid Transit will have its own lanes or priority at junctions and provide a comfortable and affordable alternative to private vehicles.

Demand Responsive Transport (DRT)

A flexible service providing shared transport to users who specify their desired location and time of pick-up/ drop-off. This could include BRT (see above).

Design code

A set of illustrated design requirements that provide specific, detailed parameters for the physical development of a site or area.

Doorstep play

Doorstep play is a commonly used phrase in housing and public space design to mean that young children can safely play on their doorstep/ close to their homes.

Car Barn

A structure that provides covered, semi-outdoor parking spaces for vehicles, typically cars, vans or motorcycles. Car bans can help to reduce the number of car along streets and provides flexibility for changing use should car ownership fall in the future.

Car-free streets

Streets that prevent the through-movement of vehicles through the use of modal filters so that cycling and walking is permitted. Car-free streets create usable public realm. Servicing and emergency access needs are met through limiting the length of the car-free zone or through the use of flexible modal filters such as rising bollards.

Climate emergency

Recognition that humanity is in a climate crisis and that organisations with decision making power have a responsibility to mitigate climate change and employ measures to slow down human-caused global warming. Epping Forest District Council declared a climate emergency in 2019 and committed to do everything within its power to become a carbon neutral District by 2030.

Community asset

Buildings, structures, spaces and land constructed or delivered as a result of the development which do not form part of residential properties, and which serve the community in some way. These 'assets' may or may not generate income.

Community engagement

A process by which the community is invited, encouraged and enabled to ensure their views are expressed and taken into account.

Density

A measure of the number of homes or the number of habitable rooms per hectare f development area.

Dual-aspect

Homes that have opening windows on two different sides, to promote good internal conditions, including sunlight at different times of day and the ability to use cross-ventilation to naturally ventilate and cool the home.

Endorsement

Where a document, such as a design code, provides further detail to policies in a Local Plan, it can be formally endorsed by Councillors. The document can then be regarded as a material consideration in future planning decisions but are not part of a development plan.

Form factor

Is the proportion of floor area to external wall area and can have a significant impact on energy efficiency. Urban building forms such as terraces and apartments minimise heat loss with a low form factor (NMDC definition).

Framework masterplan

The framework masterplan is diagrammatic and illustrates the site-wide strategies and principles of the design code. It illustrates how the design code requirements can be delivered whilst allowing flexibility for innovation and creativity in detailed design proposals.

Frontages

The side of a building fronting on to a public street or open space. A building can have more than one frontage, e.g on a corner plot. The character of frontages are determined by how they look, their relationship with the street or open space and how they are used. E.g. an active frontage is one with well-used entrances and visible activity.

Futureproofing

Design that incorporates innovative and cutting-edge technology, as well as design that anticipates future needs through flexibility and adaptability.

Green fingers

Green spaces that are smaller and narrower than the Greenway or Green Wedges, which provide wildlife habitats, sustainable drainage and local play spaces close to homes.

Green infrastructure

A network of high quality and multifunctional greenspaces, including but not limited to environmental features such as parks, public open spaces, playing fields, sports pitches, woodlands, and allotments, which are capable of delivering a wide range of environmental and quality of life benefits for local communities.

Greenway

High quality cycling and walking route connecting key destinations, including to the Sustainable Transport Corridors and the Green Wedge network. Provides safe, attractive and enjoyable transport choices which are accessible to all ages and abilities.

Green wedge

A series of open and predominantly green spaces, kept free from inappropriate development, which run through Harlow, intended to allow residents to easily access the wider countryside.

Harlow and Gilston Garden Town (HGGT)

The whole of the existing town of Harlow and the proposed new communities to be development on land allocated for that purpose in the Garden Town partners Local Plans. These comprise the Gilston Area to the north of Harlow, land to the East Of Harlow, Latton Priory to the south of Harlow and Water Lane to the west of Harlow.

Illustrative masterplan

The masterplan drawing in the Strategic masterplan framework document that is used to illustrate some of the design principles described. This masterplan is not fixed or approved as detailed elements such as block sizes and geometry will be developed as the scheme progresses.

Infrastructure

The structures, systems and facilities required to ensure that the development can function and achieve the aims of the planning policy and the Garden Town vision. This includes highways, social and community facilities, power and utilities and green infrastructure.

Landscape-led masterplan

A masterplan that responds strongly to existing landscape features including existing watercourses, topography, ecology and planting. This will result in a strong landscape network well integrated with the proposed movement networks and buildings.

Mandatory spatial principles

A series of drawings and written principles in the endorsed Strategic Masterplan Framework that set out key deliverables in future development applications, such as strategic land uses, key movement routes, landscape character and number and approximate location of access points. The strategic design code builds on these mandatory spatial principles.

Modal shift/ modal choice

Supporting and encouraging active and sustainable travel options by providing high quality bus, walking and cycling infrastructure that is safe, accessible, attractive and convenient.

National model design code (NMDC)

A national guidance document published by the Department for Levelling Up, Housing and Communities (DLUHC) in July 2021. Part I gives guidance for the coding process and Part 2 provides guidance on content for different types of code based on the National Design Guide characteristics of a well-designed place.

Nature recovery

The process of restoring natural landscapes and nature-rich spaces to help tackle the climate crisis and improve biodiversity and human health.

Net-zero/ zero carbon

Causing or resulting in no net loss of carbon dioxide into the atmosphere. A zerocarbon building is one with zero net energy consumption or zero net carbon emissions on an annual basis.

Nodes

A space at the intersection of key movement routes that can be used for activities such as meeting, play or recreation.

Passive solar design

The design of a building, including orientation, roof shape, window design and shading devices, to maximise the warming capacity of the sun in winter whilst minimising heat loss in winter and preventing overheating in summer. This maximises natural lighting, thermal comfort and efficiency of Photovoltaic technology whilst reducing the operational energy needs of a building.

Placemaking

The process of design and planning and delivering places that are of high quality, that achieve the aims of the development and that maximise the opportunities of the site to enhance the way the place is experienced.

Play-on-the-way

Play and activity along key active travel routes to encourage enjoyment of the public realm and play and activity as a part of everyday life.

Public open space

Public spaces such as parks, squares, nodes that are intended to provide social or recreation amenity and/ or landscape and biodiversity amenity.

Public realm

Any space or place within the development that is experienced by the public. Privately owned spaces can form part of the public realm if they are publicly accessible or visible by the public.

Quality Review Panel (QRP)

An independent panel of planning, architecture, urban design and construction experts set up by the Council to provide impartial expert advice to both applicants and local authorities. The Quality Review Panel's feedback is a material consideration for local authorities and the Planning Inspectorate when determining planning applications. The purpose of the Quality Review Panel is to ensure that new development is of a high quality and contributes to place making.

Sense of place

Where the arrangement of streets, spaces, building types and materials are used to create attractive, welcoming and distinctive places to live, work and visit. (NPPF definition)

Semi-mature tree

An established tree but one which has not reached its potential ultimate height and has significant growth potential. British Standards Institution definition: "Trees with an overall height in excess of 4 metres and or a stem girth measurement (circumference) of 20 centimetres or larger."

Stewardship

Ensuring that long-term community-led care of public places and community development is in place for the new buildings and neighbourhoods for a thriving community and long-term quality of life for residents.

Strategic design code

A design code that focuses on the larger elements of design such as streets and open spaces rather than specific materials or styles. These are applicable at masterplan scale or larger and should be followed by more specific and detailed codes.

Strategic design code framework

This section of the strategic design code sets out the framework for the site that the rest of the design code strategies are based on. It incorporates the mandatory spatial principles of the Strategic Masterplan Framework as well as key elements of public realm and infrastructure to meet the aims and vision for the new Community.

Strategic masterplan area

The whole of the Latton priory Strategic masterplan area as shown on Map 2.3 of the EFDC Local Plan, including the whole of the residential site allocation and the employment sites at Riddings Farm and land at Dorrington House. N.B. The Strategic Masterplan Framework and Design code scope is limited to residential site allocation area.

Strategic masterplan framework (SMF)

A strategic masterplan process requires organisations to undertake analysis and prepare strategies, and the proposals that are needed to plan for major change in a defined physical area. The strategic masterplan framework resulting from this process acts as a context from which development projects come forward. The mandatory spatial fixes in the SMF identify those elements that are essential to future development.

Suitable Alternative Natural Greenspace (SANG)

Suitable Alternative Natural Greenspace (SANG) is the name given to greenspace that is of a quality and type suitable to be used as mitigation to offset the impact of residential development and visitor pressure on Special Protection Areas (SPAs) or Special Areas of Conservation. The purpose of SANG is to provide alternative greenspace to attract visitors away from SPAs or Special Areas of Conservation.

Sustainable drainage systems (SuDS)

These are drainage systems designed to manage surface water and groundwater to sustainably reduce the potential impact of new and existing developments on flood risk.

Sustainable transport

Efficient, safe and accessible means of transport with overall low impact on the environment, including walking and cycling, low and ultra-low emission vehicles, car sharing and public transport.

Sustainable Transport Corridor (STC)

A fast direct route to the town centre, railway station and business areas for buses, walking and cycling making it quicker and more attractive than using the car for these short trips.

Topography

The shape of the surface of the land, particularly gradients and orientation, which will impact on the way that water drains, planting, views towards and from the area and the shape and position of active travel routes.

Urban greening factor (UGF)

A tool to evaluate the quantity and quality of urban greening provided by a development proposal. The UGF ascribes different factors to different types of surfaces and planting/ vegetation. The area x the factor rating contributes to the overall UGF.

Wayfinding

The ease of finding one's way around a place through well-designed buildings and public realm. Key aspects include features such as natural features, marker buildings, art or key views and a recognisable street and open space hierarchy.

Wetlands/ wetland park

An area characterised by shallow water basins and associated planting and landforms. These form part of a network of sustainable urban drainage system and can also provide peaceful amenity and learning and play opportunities.

Page number	Image	Copyright/ Author	Year	URL
Front cover	Greenway illustration	Adriette Myburgh. Edits by Epping Forest District Council	2023	https://adriettemyburgh.co.uk/
4	Design principles diagram	Jas Bhalla Works	2023	https://jasbhallaarchitects.com/
6	Key principles for healthy growth diagram	Allies and Morrison. Reproduced from the HGGT Vision document	2018	https://www.alliesandmorrison.com https://hggt.co.uk/
10	Aerial view of Latton Priory strategic masterplan area	Google Earth	2023	https://www.google.com/maps
11	Latton Priory and surrounding farmstead buildings	Allies and Morrison. Reproduced from the HGGT Design Gudie document	2018	https://www.alliesandmorrison.com https://hggt.co.uk/
13	Greenway illustration	Adriette Myburgh	2023	https://adriettemyburgh.co.uk/
13	Car-free play street illustration	Adriette Myburgh	2023	https://adriettemyburgh.co.uk/
18	Participatory design	Epping Forest District Council	2023	https://www.eppingforestdc.gov.uk/
20	Harlow Concept plan	Epping Forest District Council	-	https://www.eppingforestdc.gov.uk/
22	Hanham Hall, Bristol	HTA Design	-	https://www.hta.co.uk/
22	Jardin de l'Aqueduc, Paris	Michel Koenig	-	unknown
23	Green spine at Valley Gardens	Phil Jones Associates	-	https://pja.co.uk/
23	Central green at Lovedon Fields	Phil Jones Associates	-	https://pja.co.uk/
23	Knights Park, Eddington, Cambridge	Pollard Thomas Edwards	2023	https://www.pollardthomasedwards.co.uk/
23	Poundbury, Dorset	Phil Jones Associates	-	https://pja.co.uk/
24	Barton Park, Oxford	Simon J Harvey. Reproduced with the permission of Hill Group	-	https://www.simonharveyphotography.com/ https://www.hill.co.uk/
25	Leeds Climate Innovation District	Paul Riddle	-	https://www.paul-riddle.com/
26	Bo0I, Malmo, Sweden.	Sebastien Ludwig	-	unknown
26	Boszoom Netherlands.	Nanda Sluijsmans	2019	https://www.flickr.com/photos/nandasluijsmans/
26	Queen Elizabeth Olympic Park, Stratford, London	Palmstead Nurseries Limited 2022	2022	https://www.palmstead.co.uk/
28	Two cyclists	Phil Jones Associates	-	https://pja.co.uk/
30	Mobility hub principles diagram	Phil Jones Associates	-	https://pja.co.uk/
32	Public transport and active travel priority	Phil Jones Associates	-	https://pja.co.uk/
38	Loveden Fields, Hampshire	Phil Jones Associates	-	https://pja.co.uk/
38	Goldsmith Street, Norwich	Tim Crocker	2019	https://www.timcrocker.co.uk/
39	Loveden Fields, Hampshire	B D Landscape Architects	2018	https://bdlandarch.com/
39	Parking barn in Zutphen, Netherlands	Bluesky, Getmapping plc, Google Earth	2023	https://www.google.com/maps
40	Riverside Rd housing, Watford	Kilian O'Sulivan	-	https://www.kilianosullivan.com/
40	Knights Park, Eddington, Cambridge	Phil Jones Associates	-	https://pja.co.uk/
42	Timekeepers Square, Salford	Historic England	-	https://historicengland.org.uk/
44	Great Kneighton, Cambridge	Phil Jones Associates	-	https://pja.co.uk/
44	Knights Park, Eddington, Cambridge	Paul Riddle	2019	https://www.paul-riddle.com/
46	Goldsmith Street, Norwich	Phil Jones Associates	-	https://pja.co.uk/
46	Trent Basin, Nottingham	Phil Jones Associates	-	https://pja.co.uk/
48	Great Kneighton, Cambridge	Phil Jones Associates	-	https://pja.co.uk/
48	Street at Rennes, France	Phil Jones Associates	-	https://pja.co.uk/
50	Great Kneighton, Cambridge	Phil Jones Associates	-	https://pja.co.uk/

Page number	Image	Copyright/ Author	Year	URL
50	The Avenue, Saffron Walden	Tim Crocker	2014	https://www.timcrocker.co.uk/
53	Greenway illustration	Adriette Myburgh	2023	https://adriettemyburgh.co.uk/
55	Car-free play street illustration	Adriette Myburgh	2023	https://adriettemyburgh.co.uk/
57	Zebra/ parallel crossing	Phil Jones Associates	-	https://pja.co.uk/
57	Cycle priority crossing	Phil Jones Associates	-	https://pja.co.uk/
58	Junction at Fishgate, Preston	Phil Jones Associates	-	https://pja.co.uk/
59	French example of informal table crossing	Phil Jones Associates	-	https://pja.co.uk/
60	Integrated planter and street tree	ipv Delft	2012	https://ipvdelft.com/
60	Leonard Circus, Hackney	Hackney Council	2014	https://hackney.gov.uk/
60	Public realm in Copenhagen	Epping Forest District Council	2023	https://www.eppingforestdc.gov.uk/
60	Market building in Copenhagen	unknown	-	unknown
62	Max Roach Park, Brixton	MUF Architecture/ Art	-	http://muf.co.uk/
62	Superkillen Park, Copenhagen	Epping Forest District Council	2023	https://www.eppingforestdc.gov.uk/
62	Play space at Westfield, Stratford	Epping Forest District Council	2023	https://www.eppingforestdc.gov.uk/
66	St Chads, Tilbury	Kilian O'Sullivan	-	https://www.kilianosullivan.com/
66	Brick House, Birmingham	Greg Holmes. Reproduced with the permission of Howells	-	https://www.howells.uk/ https://www.gregholmesphoto.com/
66	Marmalade Lane, Cambridge	David Christian Photography	2021	https://www.davidmchristian.com/
66	Knights Park, Eddington, Cambridge	Simon J Harvey. Reproduced with the permission of Hill Group	-	https://www.simonharveyphotography.com/ https://www.hill.co.uk/
66	St Chads, Tilbury	Kilian O'Sulivan	-	https://www.kilianosullivan.com/
66	Great Kneighton, Cambridge	Tim Crocker	-	https://www.timcrocker.co.uk/
67	Marmalade Lane, Cambridge	Mole Architects	2018	https://www.molearchitects.co.uk/
67	The Avenue, Saffron Walden	Tim Crocker	2014	https://www.timcrocker.co.uk/
70	Charlton, Greenwich	Morley von Sternberg	-	http://www.vonsternberg.com/
70	Abode, Newhall, Harlow	Tim Crocker	-	https://www.timcrocker.co.uk/
72	Wilkinsons Brook, Tyrellstown, Ireland	Proctor & Matthews Architects	-	https://www.proctorandmatthews.com/
72	Knights Park, Eddington, Cambridge	Paul Riddle	2019	https://www.paul-riddle.com/
72	Southwold	Eric Orme. Reproduced with the permission of Ash Sakula Architects	2019	https://place-photography.com/ https://www.ashsak.com/
74	Extract from Harlow Town Centre Framework SPD	Urban Initiatives Ltd. Reproduced from the Harlow Town Centre Framework SPD	2022	https://www.harlow.gov.uk/
74	Extract from Old Harlow Conservation Area appraisal	Harlow District Council. Reproduced from the Old Harlow Conservation Area Character Appraisal	2013	https://www.harlow.gov.uk/
74	Abode Newhall, Harlow	Tim Crocker	-	https://www.timcrocker.co.uk/
75	Torrells Hall, Willingale, Ongar	Bluesky, Getmapping plc, Google Earth	2023	https://www.google.com/maps
75	Stonards Farm, Stonards Hill, Epping	Bluesky, Getmapping plc, Google Earth	2023	https://www.google.com/maps
75	The Avenue, Saffron Walden	Tim Crocker	2014	https://www.timcrocker.co.uk/
76	Goldsmith Street, Norwich	Tim Crocker	2019	https://www.timcrocker.co.uk/
76	Seating and tree planting for shade	Streetlife	2022	https://www.streetlife.nl/us
77	Community hub, Hammersmith and Fulham	Francisco Ibáñez Hantke. Reproduced with the permission of RCKa architects	2021	https://rcka.co.uk/



Epping Forest District Council Civic Offices, 323 High Street, Epping, CM16 4BZ T 01992 564000 www.eppingforestdc.gov.uk

